

SAFETY DATA SHEET

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: EDM3 Rechargeable Battery 3.5V
MFR #: 1-220, 1-230"
DISTRIBUTED BY: EDM3, LLC
 3611 St Johns Bluff Road, Suite 1
 Jacksonville, FL 32224

INFORMATION LINE: 1-800-638-2625
 Monday – Friday 8:00 a.m. – 5:00 p.m. EST

EMERGENCY PHONE: 1-800-424-9300 (CHEMTREC)
 Day or night

PRODUCT DESCRIPTION: N/A

SECTION 2: HAZARDS IDENTIFICATION

No specific health hazards for normal use.

ROUTES OF ENTRY: Eyes, Skin, Inhalation, Ingestion.

2

Health Hazards

These chemicals are contained in a sealed can. Risk of exposure occurs only if the battery is mechanically or electrically abused. The most likely risk is acute exposure when a battery vents. Leaking material exposure to skin, eyes may cause irritation. Inhalation of fumes may cause respiratory irritation.

Sign/Symptoms of Exposure

Leaking can cause thermal and chemical burns upon contact with the skin.

SECTION 3: COMPOSITION/INFORMATION OF INGREDIENTS

Chemical Name	Molecular Formula	CAS No.	Weight (%)
Nickel Hydroxide	Ni(OH) ₂	12054-48-7	29
Cobaltous Oxide	CoO	1307-96-6	5
Steel	Fe	7439-89-6	8
Nickel	Ni	7440-02-0	10
PVC	(C ₂ H ₃ Cl) _n	9002-86-2	5
Potassium Hydroxide (Liquid)	KOH	1310-58-3	3
Sodium Hydroxide	NaOH	1310-73-2	2
Polypropylene	(C ₃ H ₆) _n	9003-07-0	3
Rare Earth Alloy	----	-----	35

SECTION 4: FIRST-AID MEASURES

- EYES:** Flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical aid.
- SKIN:** Remove contaminated clothes and rinse skin with plenty of water or shower for 15 minutes. Get medical aid.
- INGESTION:** Do not induce vomiting. Call a physician immediately.
- INHALATION:** Remove from exposure and move to fresh air immediately. Use oxygen if available.

SECTION 5: FIRE-FIGHTING MEASURES

- Flash Point:** N/A.
- Auto-Ignition Temperature:** N/A.
- Extinguishing Media:** CO₂ dry chemical.
- Special Fire-Fighting Procedures:** Self-contained breathing apparatus.
- Unusual Fire and Explosion Hazards:** Cell may vent when subjected to excessive heat-exposing battery contents.
- Hazardous Combustion Products:** Carbon monoxide, carbon dioxide, other metallic oxide fumes.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Steps to be Taken in case Material is Released or Spilled

If the battery is accidental broken and leaks out, wipe it up with a cloth, and dispose of it in a plastic bag and put into a steel can. The preferred response is to leave the area and allow the batteries to cool and vapors to dissipate. Provide maximum ventilation. Avoid skin and eye contact or inhalation of vapors. Remove spilled material with absorbent.

Waste Disposal Method

It is recommended to discharge the battery to the end, recycle zinc, copper and other metal, handing in the abandoned batteries to related department unified, dispose of the batteries in accordance with approved local, state, and federal requirements. Consult state environmental protection agency and/or federal EPA.

SECTION 7: HANDLING AND STORAGE

The batteries should not be opened, destroyed or incinerate, since they may leak or rupture and release to the environment the ingredients that they contain in the hermetically sealed container. Do not short circuit terminals, or charge the battery, forced over-discharge, throw to fire. Do not crush or puncture the battery, or immerse in liquids.

Precautions to be taken in handling and storing

Avoid mechanical or electrical abuse. Storage preferably in cool, dry and ventilated area, which is subject to little temperature change. Storage at high temperatures should be avoided. Do not place the battery near heating equipment, nor expose to direct sunlight for long periods.

Other Precautions

Do not short or install with incorrect polarity.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Respiratory Protection

In case of battery venting, provide as much ventilation as possible. Avoid confined areas with venting batteries. Respiratory Protection is not necessary under conditions of normal use.

Other Protective Clothing or Equipment

Not necessary under conditions of normal use.

Personal Protection is recommended for venting batteries: Respiratory Protection, Protective Gloves, Protective Clothing and Safety Glass with side shields.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Nominal Voltage: 2.4V

Rated Capacity: 800MAH

Appearance Characters: Green with odorless cylindrical battery.

Chemical Uses: Low voltage power supply.

SECTION 10: STABILITY AND REACTIVITY

STABILITY: Stable

CONDITIONS TO AVOID (STABILITY): Heating, fire, mechanical abuse and electrical abuse.

HAZARDOUS DECOMPOSITION OR BY-PRODUCTS: When exposed to fire or extreme heat, batteries may emit toxic fumes.

SECTION 11: TOXICOLOGICAL INFORMATION

Inhalation, skin contact and eye contact are possible when the battery is opened. Exposure to internal contents, the corrosive fumes will be irritation to skin, eyes and mucous membranes. Overexposure can cause symptoms of non-fibroid lung injury and membrane irritation.

SECTION 12: ECOLOGICAL INFORMATION

Environment Effect

When promptly used or disposed the battery does not present environmental hazard. When disposed, keep away from water, rain and snow.

SECTION 13: DISPOSAL CONSIDERATIONS

Appropriate Method of Disposal of Substance or Preparation

Dispose of the batteries in accordance with approved local, state, and federal requirements. Consult state environmental agency.

SECTION 14: TRANSPORT INFORMATION

NI-CD BATTERY is exempt from dangerous goods. It is considered non-dangerous goods by the international Civil Aviation Organization (ICAO), the International Air Transport Association (IATA) DGR 56th, International Maritime Dangerous Goods regulations (IMDG), or Recommendations on the Transport of Dangerous Goods Model Regulations.

The only DOT requirements for shipping Nickel Cadmium batteries is Special Provision A123 under 56th which states: "Batteries, dry are not subject to the requirements of this subchapter only when they are offered for transportation in a manner that prevents the dangerous evolution of heat.

Separate batteries when shipping to prevent short-circuiting. They should be packed in strong packaging for support during transport.

Transport Fashion: By air, by sea, by railway, by road.

SECTION 15: REGULATORY INFORMATION

Law Information

- 《Dangerous Goods Regulation》
- 《Recommendations on the Transport of Dangerous Goods Model Regulations》
- 《International Maritime Dangerous Goods》
- 《Technical Instructions for the Safe Transport of Dangerous Goods》
- 《Classification and code of dangerous goods》
- 《Occupational Safety and Health Act》 (OSHA)
- 《Toxic Substances Control Act》 (TSCA)
- 《Consumer Product Safety Act》 (CPSA)
- 《Federal Environmental Pollution Control Act》 (FEPCA)
- 《The Oil Pollution Act》 (OPA)
- 《Superfund Amendments and Reauthorization Act Title III (302/311/312/313)》 (SARA)
- 《Resource Conservation and Recovery Act》 (RCRA)
- 《Safety Drinking Water Act》 (CWA)
- 《California Proposition 65》
- 《Code of Federal Regulations》 (CFR)

In accordance with all Federal, State and Local laws.

SECTION 16: OTHER INFORMATION



SDS DATE: 01/05/2015

The above information is based on the data of which we are aware and is believed to be correct as of the data hereof. Since this information may be applied under conditions beyond our control and with which may be unfamiliar and since data made available subsequent to the data hereof may suggest modifications of the information, we do not assume any responsibility for the results of its use. This information is furnished upon condition that the person receiving it shall make his own determination of the suitability of the material for his particular purpose.