

SECTION 1: Identification

1.1. Identification

Product form : Mixture
Product name : Acrylic Mounting Medium
Product code : 400616, 400691

1.2. Recommended use and restrictions on use

Use of the substance/mixture : For laboratory and manufacturing use only
For professional use only
Restrictions on use : Not for food, drug or household use

1.3. Supplier

EDM 3, LLC
3611 St Johns Bluff Road, Suite 1
Jacksonville, FL 32224
T 800-638-2625, Monday-Friday: 8:00 AM-5:00 PM

1.4. Emergency telephone number

Emergency number : INFOTRAC at 1-800-535-5053 (Domestic within the USA and Canada) or 1-352-323-3500
(International callers may call collect), 24 hours/day, 7 days/week.

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS US classification

Flammable liquids Category 2	H225	Highly flammable liquid and vapor
Skin corrosion/irritation Category 2	H315	Causes skin irritation
Reproductive toxicity Category 1B	H360	May damage fertility or the unborn child
Specific target organ toxicity – Single exposure, Category 3, Narcosis	H336	May cause drowsiness or dizziness
Specific target organ toxicity (repeated exposure) Category 2	H373	May cause damage to organs through prolonged or repeated exposure

Full text of H statements : see section 16

2.2. GHS Label elements, including precautionary statements

GHS US labeling

Hazard pictograms (GHS US) :



Signal word (GHS US) :

Danger

Hazard statements (GHS US) :

H225 - Highly flammable liquid and vapor
H315 - Causes skin irritation
H336 - May cause drowsiness or dizziness
H360 - May damage fertility or the unborn child
H373 - May cause damage to organs through prolonged or repeated exposure

Precautionary statements (GHS US) :

P201 - Obtain special instructions before use.
P202 - Do not handle until all safety precautions have been read and understood.
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Acrylic Mounting Medium

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P233 - Keep container tightly closed.
P240 - Ground/Bond container and receiving equipment.
P241 - Use explosion-proof electrical/ventilating/lighting equipment.
P242 - Use only non-sparking tools.
P243 - Take precautionary measures against static discharge.
P260 - Do not breathe dust/fume/gas/mist/vapors/spray.
P261 - Avoid breathing dust/fume/gas/mist/vapors/spray.
P264 - Wash hands, forearms and face thoroughly after handling.
P271 - Use only outdoors or in a well-ventilated area.
P280 - Wear protective gloves/protective clothing/eye protection/face protection.
P302+P352 - If on skin: Wash with plenty of water.
P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing.
P308+P313 - If exposed or concerned: Get medical advice/attention.
P312 - Call a poison center or doctor if you feel unwell.
P314 - Get medical advice/attention if you feel unwell.
P321 - Specific treatment (see supplemental first aid instruction on this label).
P332+P313 - If skin irritation occurs: Get medical advice/attention.
P362+P364 - Take off contaminated clothing and wash it before reuse.
P370+P378 - In case of fire: Use media other than water to extinguish.
P403+P233 - Store in a well-ventilated place. Keep container tightly closed.
P403+P235 - Store in a well-ventilated place. Keep cool.
P405 - Store locked up.
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS US)

No additional information available

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	Conc.	GHS US classification
toluene	CAS-No.: 108-88-3	65 – 69.29	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Repr. 2, H361 STOT SE 3, H336 STOT RE 2, H373 Asp. Tox. 1, H304
acrylic polymers (non-hazardous)	-	25.48 – 29	Not classified
2,6-di-tert-butyl-p-cresol	CAS-No.: 128-37-0	< 1	Not classified
benzyl butyl phthalate	CAS-No.: 85-68-7	< 1	Repr. 1B, H360

Acrylic Mounting Medium

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Name	Product identifier	Conc.	GHS US classification
isobutyl methacrylate	CAS-No.: 97-86-9	< 0.029	Flam. Liq. 3, H226 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 STOT SE 3, H335
dibutyl phthalate	CAS-No.: 84-74-2	< 0.01	Repr. 1B, H360

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures general	: IF exposed or concerned: Get medical advice/attention.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing. If skin irritation occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse eyes with water as a precaution.
First-aid measures after ingestion	: Call a poison center/doctor/physician if you feel unwell.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects	: May cause drowsiness or dizziness.
Symptoms/effects after inhalation	: Although no appropriate human or animal health effects data are known to exist, this material is expected to be an inhalation hazard.
Symptoms/effects after skin contact	: Irritation.
Symptoms/effects after eye contact	: None under normal conditions.
Symptoms/effects after ingestion	: None under normal conditions.
Chronic symptoms	: May damage fertility or the unborn child.

4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media	: Do not use a heavy water stream.

5.2. Specific hazards arising from the chemical

Fire hazard	: Highly flammable liquid and vapor.
Explosion hazard	: No direct explosion hazard.
Hazardous decomposition products in case of fire	: Toxic fumes may be released.

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions	: Fight fire from safe distance and protected location. Do not enter fire area without proper protective equipment, including respiratory protection.
Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

Acrylic Mounting Medium

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Stop leak if safe to do so. Notify authorities if product enters sewers or public waters. Absorb spillage to prevent material-damage.

6.1.1. For non-emergency personnel

Protective equipment : Wear recommended personal protective equipment.
Emergency procedures : No open flames, no sparks, and no smoking. Only qualified personnel equipped with suitable protective equipment may intervene. Do not breathe dust/fume/gas/mist/vapors/spray.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
Emergency procedures : Evacuate unnecessary personnel. Stop leak if safe to do so.

6.2. Environmental precautions

Avoid release to the environment. Notify authorities if product enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

For containment : Absorb spilled material with sand or earth. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Stop leak, if possible without risk.
Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.
Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : Not expected to present a significant hazard under anticipated conditions of normal use.
Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapors may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapors/spray. Use only outdoors or in a well-ventilated area. Avoid contact with skin and eyes.
Hygiene measures : Separate working clothes from town clothes. Launder separately. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Ground/bond container and receiving equipment.
Storage conditions : Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.
Packaging materials : Store always product in container of same material as original container.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Acrylic Mounting Medium

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

toluene (108-88-3)

USA - ACGIH - Occupational Exposure Limits

ACGIH OEL TWA 20 ppm

2,6-di-tert-butyl-p-cresol (128-37-0)

USA - ACGIH - Occupational Exposure Limits

ACGIH OEL TWA 2 mg/m³ (Inhalable fraction and vapor)

dibutyl phthalate (84-74-2)

USA - ACGIH - Occupational Exposure Limits

ACGIH OEL TWA 5 mg/m³

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.
Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:

Wear recommended personal protective equipment.

Hand protection:

Protective gloves

Eye protection:

Safety glasses

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

[In case of inadequate ventilation] wear respiratory protection.

Personal protective equipment symbol(s):



SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid
Appearance : Colorless liquid.
Color : No data available
Odor : Pungent
Odor threshold : No data available
pH : No data available
Melting point : Not applicable
Freezing point : No data available
Boiling point : No data available
Flash point : No data available
Relative evaporation rate (butyl acetate=1) : No data available

Acrylic Mounting Medium

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Flammability (solid, gas)	: No data available
Vapor pressure	: No data available
Relative vapor density at 20°C	: No data available
Relative density	: No data available
Density	: 0.93 g/ml
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available

toluene	
Boiling point	111 °C (1013 hPa)
Flash point	4.4 °C (Closed cup, 1013 hPa)
Auto-ignition temperature	480 °C (1013 hPa, T1)
Vapor pressure	30.89 hPa (21 °C)
Vapor pressure at 50°C	109 hPa

2,6-di-tert-butyl-p-cresol	
Boiling point	266 °C (1013 hPa)
Flash point	127 °C (Closed cup, 1013 hPa)
Auto-ignition temperature	No data available in the literature
Vapor pressure	< 0.01 hPa (24.85 °C, OECD 104: Vapour Pressure)
Vapor pressure at 50°C	0.16 hPa

isobutyl methacrylate	
Boiling point	155 °C (1025 hPa, EU Method A.2: Boiling point)
Flash point	43 °C (Closed cup, 1013 hPa, EU Method A.9: Flash-Point)
Auto-ignition temperature	385 °C (1013 hPa, T2)
Vapor pressure	2.1 hPa (20 °C, Equivalent or similar to OECD 104)

benzyl butyl phthalate	
Boiling point	370 °C
Flash point	198 °C (1013 hPa)
Auto-ignition temperature	425 °C (T2)
Vapor pressure	0.000011 hPa (25 °C, Equivalent or similar to OECD 104)

dibutyl phthalate	
Boiling point	340 °C (1013 hPa)
Flash point	187 °C (Open cup, 995 hPa, ISO 2592)
Auto-ignition temperature	390 °C (1000 hPa, DIN 51794 (2003), T2)

Acrylic Mounting Medium

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

dibutyl phthalate

Vapor pressure	0.000097 hPa (25 °C)
----------------	----------------------

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Highly flammable liquid and vapor.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

toluene (108-88-3)

LD50 oral rat	5580 mg/kg body weight (Equivalent or similar to EU Method B.1, Rat, Male, Experimental value, Oral, 7 day(s))
LD50 dermal rabbit	> 5000 mg/kg body weight (24 h, Rabbit, Male, Experimental value, Dermal)
LC50 Inhalation - Rat	28.1 mg/l air (Equivalent or similar to OECD 403, 4 h, Rat, Male / female, Experimental value, Inhalation (vapours))
ATE US (oral)	5580 mg/kg body weight

2,6-di-tert-butyl-p-cresol (128-37-0)

LD50 oral rat	> 6000 mg/kg body weight (OECD 401: Acute Oral Toxicity, Rat, Male / female, Experimental value, Oral, 14 day(s))
LD50 dermal rat	> 2000 mg/kg body weight (OECD 402: Acute Dermal Toxicity, 24 h, Rat, Male / female, Experimental value, Dermal, 14 day(s))

Acrylic Mounting Medium

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

isobutyl methacrylate (97-86-9)	
LD50 oral rat	9590 mg/kg body weight (Equivalent or similar to OECD 401, Rat, Male / female, Experimental value, Oral, 14 day(s))
LD50 dermal	> 17760 mg/kg body weight (Guinea pig, Dermal)
ATE US (oral)	9590 mg/kg body weight
benzyl butyl phthalate (85-68-7)	
LD50 oral rat	2330 mg/kg body weight (Equivalent or similar to OECD 401, Rat, Male / female, Experimental value, Oral, 14 day(s))
LD50 dermal rabbit	> 10000 mg/kg body weight (24 h, Rabbit, Male / female, Experimental value, Dermal, 14 day(s))
ATE US (oral)	2330 mg/kg body weight
dibutyl phthalate (84-74-2)	
LD50 oral rat	6279 mg/kg body weight (Equivalent or similar to OECD 401, Rat, Male / female, Experimental value, Oral, 7 day(s))
LC50 Inhalation - Rat	≥ 15.58 mg/l (4 h, Rat, Male / female, Experimental value, Inhalation (aerosol), 14 day(s))
ATE US (oral)	6279 mg/kg body weight
Skin corrosion/irritation	: Causes skin irritation.
toluene (108-88-3)	
pH	No data available in the literature
2,6-di-tert-butyl-p-cresol (128-37-0)	
pH	No data available in the literature
isobutyl methacrylate (97-86-9)	
pH	No data available in the literature
Serious eye damage/irritation	: Not classified
toluene (108-88-3)	
pH	No data available in the literature
2,6-di-tert-butyl-p-cresol (128-37-0)	
pH	No data available in the literature
isobutyl methacrylate (97-86-9)	
pH	No data available in the literature
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
toluene (108-88-3)	
IARC group	3 - Not classifiable
Reproductive toxicity	: May damage fertility or the unborn child.
STOT-single exposure	: May cause drowsiness or dizziness.
toluene (108-88-3)	
STOT-single exposure	May cause drowsiness or dizziness.

Acrylic Mounting Medium

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

isobutyl methacrylate (97-86-9)	
STOT-single exposure	May cause respiratory irritation.
STOT-repeated exposure	: May cause damage to organs through prolonged or repeated exposure.
toluene (108-88-3)	
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.
Aspiration hazard	: Not classified
Viscosity, kinematic	: No data available
toluene (108-88-3)	
Viscosity, kinematic	No data available in the literature
2,6-di-tert-butyl-p-cresol (128-37-0)	
Viscosity, kinematic	3.47 mm ² /s (0 °C, ASTM D445: Capillary viscometer)
isobutyl methacrylate (97-86-9)	
Viscosity, kinematic	1.01 mm ² /s (20 °C, Equivalent or similar to OECD 114)
benzyl butyl phthalate (85-68-7)	
Viscosity, kinematic	37.736 mm ² /s
dibutyl phthalate (84-74-2)	
Viscosity, kinematic	18.8 mm ² /s (20 °C, ASTM D445: Capillary viscometer)
Symptoms/effects	: May cause drowsiness or dizziness.
Symptoms/effects after inhalation	: Although no appropriate human or animal health effects data are known to exist, this material is expected to be an inhalation hazard.
Symptoms/effects after skin contact	: Irritation.
Symptoms/effects after eye contact	: None under normal conditions.
Symptoms/effects after ingestion	: None under normal conditions.
Chronic symptoms	: May damage fertility or the unborn child.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms or to cause long-term adverse effects in the environment.

toluene (108-88-3)	
LC50 - Fish [1]	5.5 mg/l (96 h, Oncorhynchus kisutch, Flow-through system, Fresh water, Experimental value, Lethal)
2,6-di-tert-butyl-p-cresol (128-37-0)	
LC50 - Fish [1]	0.199 mg/l (ECOSAR v1.00, 96 h, Pisces, QSAR, Lethal)
EC50 - Crustacea [1]	0.48 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, GLP)
EC50 72h - Algae [1]	> 0.24 mg/l (OECD 201: Alga, Growth Inhibition Test, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, Growth rate)
isobutyl methacrylate (97-86-9)	
LC50 - Fish [1]	20 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Oncorhynchus mykiss, Flow-through system, Fresh water, Experimental value, Lethal)

Acrylic Mounting Medium

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

isobutyl methacrylate (97-86-9)	
EC50 - Crustacea [1]	> 29 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Flow-through system, Fresh water, Experimental value, Locomotor effect)
ErC50 algae	16 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Pseudokirchneriella subcapitata, Fresh water, Experimental value, GLP)
benzyl butyl phthalate (85-68-7)	
LC50 - Fish [1]	0.51 mg/l (ASTM E729-80, 96 h, Cymatogaster aggregata, Flow-through system, Salt water, Experimental value, Lethal)
EC50 72h - Algae [1]	1.5 mg/l (OECD 201: Alga, Growth Inhibition Test, Desmodesmus subspicatus, Static system, Fresh water, Experimental value, Growth rate)
dibutyl phthalate (84-74-2)	
LC50 - Fish [1]	0.92 mg/l (Equivalent or similar to OECD 203, 96 h, Lepomis macrochirus, Static system, Fresh water, Experimental value, GLP)
EC50 - Crustacea [1]	2.99 mg/l (EPA OPPTS 850.1035, 48 h, Daphnia magna, Static system, Experimental value, Lethal)

12.2. Persistence and degradability

Acrylic Mounting Medium	
Persistence and degradability	Not rapidly degradable
toluene (108-88-3)	
Persistence and degradability	Readily biodegradable in water.
Biochemical oxygen demand (BOD)	2.15 g O ₂ /g substance
Chemical oxygen demand (COD)	2.52 g O ₂ /g substance
ThOD	3.13 g O ₂ /g substance
2,6-di-tert-butyl-p-cresol (128-37-0)	
Persistence and degradability	Not readily biodegradable in water.
Biochemical oxygen demand (BOD)	0.51 g O ₂ /g substance
Chemical oxygen demand (COD)	2.27 g O ₂ /g substance
ThOD	2.977 g O ₂ /g substance
isobutyl methacrylate (97-86-9)	
Persistence and degradability	Readily biodegradable in water.
acrylic polymers (non-hazardous)	
Persistence and degradability	Not rapidly degradable
benzyl butyl phthalate (85-68-7)	
Persistence and degradability	Biodegradability in soil: no data available, Readily biodegradable in water.
dibutyl phthalate (84-74-2)	
Persistence and degradability	Biodegradable in the soil, Readily biodegradable in water.
Biochemical oxygen demand (BOD)	0.43 g O ₂ /g substance
ThOD	2.24 g O ₂ /g substance

Acrylic Mounting Medium

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

12.3. Bioaccumulative potential

toluene (108-88-3)	
BCF - Fish [1]	90 (3 day(s), Leuciscus idus, Static renewal, Fresh water, Experimental value, Fresh weight)
Partition coefficient n-octanol/water (Log Pow)	2.73 (Experimental value, 20 °C)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).
2,6-di-tert-butyl-p-cresol (128-37-0)	
Partition coefficient n-octanol/water (Log Pow)	5.1
Bioaccumulative potential	Potential for bioaccumulation ($4 \leq \text{Log Kow} \leq 5$).
isobutyl methacrylate (97-86-9)	
Partition coefficient n-octanol/water (Log Pow)	2.95 (Experimental value, Equivalent or similar to OECD 107, 20 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).
benzyl butyl phthalate (85-68-7)	
BCF - Fish [1]	12.4 (Equivalent or similar to OECD 305, 3.27 day(s), Lepomis macrochirus, Flow-through system, Fresh water, Experimental value)
BCF - Fish [2]	9.4 (OECD 305: Bioconcentration: Flow-Through Fish Test, Lepomis macrochirus, Flow-through system, Fresh water, Experimental value)
BCF - Other aquatic organisms [1]	26 – 270
Partition coefficient n-octanol/water (Log Pow)	4.91 (Practical experience/observation, OECD 107: Partition Coefficient (n-octanol/water): Shake Flask Method, 20 °C)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).
dibutyl phthalate (84-74-2)	
BCF - Fish [1]	1.8 l/kg (OECD 305: Bioconcentration: Flow-Through Fish Test, 28 day(s), Cyprinus carpio, Experimental value)
Partition coefficient n-octanol/water (Log Pow)	4.46 (Experimental value, EU Method A.8: Partition Coefficient, 30 °C)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).

12.4. Mobility in soil

toluene (108-88-3)	
Surface tension	27.73 mN/m (25 °C, 0.05 %)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	2.3 (log Koc, Calculated value)
Ecology - soil	Low potential for adsorption in soil.
2,6-di-tert-butyl-p-cresol (128-37-0)	
Surface tension	Not applicable (water solubility < 1 mg/l)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	4.4 (log Koc, SRC PCKOCWIN v1.66, Calculated value)
Ecology - soil	Low potential for mobility in soil. May be harmful to plant growth, blooming and fruit formation.
isobutyl methacrylate (97-86-9)	
Surface tension	No data available in the literature

Acrylic Mounting Medium

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

isobutyl methacrylate (97-86-9)	
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	3.44 (log Koc, Calculated value)
Ecology - soil	Low potential for mobility in soil.
benzyl butyl phthalate (85-68-7)	
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	3.41 (log Koc, SRC PCKOCWIN v2.0, QSAR)
Ecology - soil	Low potential for adsorption in soil.
dibutyl phthalate (84-74-2)	
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	3.0635 (log Koc, SRC PCKOCWIN v2.0, QSAR)
Ecology - soil	Low potential for mobility in soil.

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Disposal methods

Regional waste regulation	: Disposal must be done according to official regulations.
Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Sewage disposal recommendations	: Disposal must be done according to official regulations.
Product/Packaging disposal recommendations	: Disposal must be done according to official regulations.
Additional information	: Flammable vapors may accumulate in the container. Do not re-use empty containers.

SECTION 14: Transport information

In accordance with DOT / TDG / IMDG / IATA

14.1. UN number

UN-No. (DOT)	: UN1294
UN-No. (TDG)	: UN1294
UN-No. (IMDG)	: 1294
UN-No. (IATA)	: 1294

14.2. UN proper shipping name

Proper Shipping Name (DOT)	: Toluene
Proper Shipping Name (TDG)	: TOLUENE
Proper Shipping Name (IMDG)	: TOLUENE
Proper Shipping Name (IATA)	: Toluene

14.3. Transport hazard class(es)

DOT

Transport hazard class(es) (DOT)	: 3
Hazard labels (DOT)	: 3

Acrylic Mounting Medium

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations



TDG

Transport hazard class(es) (TDG) : 3
Hazard labels (TDG) : 3



IMDG

Transport hazard class(es) (IMDG) : 3
Hazard labels (IMDG) : 3



IATA

Transport hazard class(es) (IATA) : 3
Hazard labels (IATA) : 3



14.4. Packing group

Packing group (DOT) : II
Packing group (TDG) : II
Packing group (IMDG) : II
Packing group (IATA) : II

14.5. Environmental hazards

Other information : No supplementary information available.

14.6. Special precautions for user

DOT
UN-No.(DOT) : UN1294
DOT Special Provisions (49 CFR 172.102) : IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized.
T4 - 2.65 178.274(d)(2) Normal..... 178.275(d)(3)
TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = $97 / 1 + a (tr - tf)$ Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling.
DOT Packaging Exceptions (49 CFR 173.xxx) : 150
DOT Packaging Non Bulk (49 CFR 173.xxx) : 202
DOT Packaging Bulk (49 CFR 173.xxx) : 242
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : 5 L
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 60 L

Acrylic Mounting Medium

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

DOT Vessel Stowage Location : B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this section is exceeded.

TDG

UN-No. (TDG) : UN1294
Explosive Limit and Limited Quantity Index : 1 L
Excepted quantities (TDG) : E2
Passenger Carrying Road Vehicle or Passenger Carrying Railway Vehicle Index : 5 L
Emergency Response Guide (ERG) Number : 130

IMDG

Limited quantities (IMDG) : 1 L
Excepted quantities (IMDG) : E2
Packing instructions (IMDG) : P001
IBC packing instructions (IMDG) : IBC02
Tank instructions (IMDG) : T4
Tank special provisions (IMDG) : TP1
EmS-No. (Fire) : F-E - FIRE SCHEDULE Echo - NON-WATER-REACTIVE FLAMMABLE LIQUIDS
EmS-No. (Spillage) : S-D - SPILLAGE SCHEDULE Delta - FLAMMABLE LIQUIDS
Stowage category (IMDG) : B
Flash point (IMDG) : 7°C c.c.
Properties and observations (IMDG) : Colourless liquid with a benzene-like odour. Flashpoint: 7°C c.c. Explosive limits: 1.27% to 7%. Immiscible with water.

IATA

PCA Excepted quantities (IATA) : E2
PCA Limited quantities (IATA) : Y341
PCA limited quantity max net quantity (IATA) : 1L
PCA packing instructions (IATA) : 353
PCA max net quantity (IATA) : 5L
CAO packing instructions (IATA) : 364
CAO max net quantity (IATA) : 60L
ERG code (IATA) : 3L

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory, except for:

2,6-di-tert-butyl-p-cresol	CAS-No. 128-37-0	< 1%
acrylic polymers (non-hazardous)	CAS-No.	25.48 – 29%
benzyl butyl phthalate	CAS-No. 85-68-7	< 1%
dibutyl phthalate	CAS-No. 84-74-2	< 0.01%

Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.

Acrylic Mounting Medium

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

toluene	CAS-No. 108-88-3	65 – 69.29%
---------	------------------	-------------

toluene (108-88-3)

Listed on EPA Hazardous Air Pollutant (HAPS)

CERCLA RQ	1000 lb
-----------	---------

15.2. International regulations

CANADA

toluene (108-88-3)

Listed on the Canadian DSL (Domestic Substances List)

isobutyl methacrylate (97-86-9)

Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

No additional information available

National regulations

toluene (108-88-3)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

isobutyl methacrylate (97-86-9)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

15.3. US State regulations



WARNING:

This product can expose you to Toluene, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Component	State or local regulations
toluene(108-88-3)	U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List
isobutyl methacrylate(97-86-9)	U.S. - New Jersey - Right to Know Hazardous Substance List

SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Full text of hazard classes and H-statements	
H225	Highly flammable liquid and vapor
H226	Flammable liquid and vapor
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H317	May cause an allergic skin reaction

Acrylic Mounting Medium

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Full text of hazard classes and H-statements	
H319	Causes serious eye irritation
H335	May cause respiratory irritation
H336	May cause drowsiness or dizziness
H360	May damage fertility or the unborn child
H361	Suspected of damaging fertility or the unborn child
H373	May cause damage to organs through prolonged or repeated exposure

NFPA health hazard


: 2 - Materials that, under emergency conditions, can cause temporary incapacitation or residual injury.

NFPA fire hazard

: 3 - Liquids and solids (including finely divided suspended solids) that can be ignited under almost all ambient temperature conditions.

NFPA reactivity

: 0 - Material that in themselves are normally stable, even under fire conditions.



Safety Data Sheet (SDS), USA

The above information is believed to be correct but does not purport to be all-inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. EDM3 shall not be liable for any damage resulting from handling.