

### SECTION 1: Identification

#### 1.1. Identification

Product form : Mixture  
Product name : Formaldehyde 37%  
Product code : 400469, 400529

#### 1.2. Recommended use and restrictions on use

Use of the substance/mixture : For laboratory and manufacturing use only  
For professional use only  
Restrictions on use : Not for food, drug or household use

#### 1.3. Supplier

EDM 3, LLC  
3611 St Johns Bluff Road, Suite 1  
Jacksonville, FL 32224  
T 800-638-2625, Monday-Friday: 8:00 AM-5:00 PM

#### 1.4. Emergency telephone number

Emergency number : INFOTRAC at 1-800-535-5053 (Domestic within the USA and Canada) or 1-352-323-3500  
(International callers may call collect), 24 hours/day, 7 days/week.

### SECTION 2: Hazard(s) identification

#### 2.1. Classification of the substance or mixture

##### GHS US classification

Flammable liquids Category 3	H226	Flammable liquid and vapor
Acute toxicity (oral) Category 3	H301	Toxic if swallowed
Acute toxicity (dermal) Category 3	H311	Toxic in contact with skin
Acute toxicity (inhalation:dust,mist) Category 4	H332	Harmful if inhaled
Skin corrosion/irritation Category 1B	H314	Causes severe skin burns and eye damage
Serious eye damage/eye irritation Category 1	H318	Causes serious eye damage
Skin sensitization, Category 1	H317	May cause an allergic skin reaction
Germ cell mutagenicity Category 2	H341	Suspected of causing genetic defects
Carcinogenicity Category 1A	H350	May cause cancer
Specific target organ toxicity (single exposure) Category 1	H370	Causes damage to organs
Specific target organ toxicity – Single exposure, Category 3, Narcosis	H336	May cause drowsiness or dizziness
Full text of H statements : see section 16		

#### 2.2. GHS Label elements, including precautionary statements

##### GHS US labeling

Hazard pictograms (GHS US) :



Signal word (GHS US) :

Danger

Hazard statements (GHS US) :

H226 - Flammable liquid and vapor  
H301+H311 - Toxic if swallowed or in contact with skin  
H314 - Causes severe skin burns and eye damage  
H317 - May cause an allergic skin reaction

# Formaldehyde 37%

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Precautionary statements (GHS US)	: H318 - Causes serious eye damage H332 - Harmful if inhaled H336 - May cause drowsiness or dizziness H341 - Suspected of causing genetic defects H350 - May cause cancer H370 - Causes damage to organs P201 - Obtain special instructions before use. P202 - Do not handle until all safety precautions have been read and understood. P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P233 - Keep container tightly closed. P240 - Ground/Bond container and receiving equipment. P241 - Use explosion-proof electrical/ventilating/lighting equipment. P242 - Use only non-sparking tools. P243 - Take precautionary measures against static discharge. P260 - Do not breathe dust/fume/gas/mist/vapors/spray. P261 - Avoid breathing dust/fume/gas/mist/vapors/spray. P264 - Wash hands, forearms and face thoroughly after handling. P270 - Do not eat, drink or smoke when using this product. P271 - Use only outdoors or in a well-ventilated area. P272 - Contaminated work clothing must not be allowed out of the workplace. P280 - Wear protective gloves/protective clothing/eye protection/face protection. P301+P310 - If swallowed: Immediately call a poison center or doctor. P301+P330+P331 - If swallowed: rinse mouth. Do NOT induce vomiting. P302+P352 - If on skin: Wash with plenty of water. P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing. P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P307+P311 - If exposed: Call a poison center/doctor. P308+P313 - If exposed or concerned: Get medical advice/attention. P310 - Immediately call a poison center or doctor. P312 - Call a poison center or doctor if you feel unwell. P321 - Specific treatment (see supplemental first aid instruction on this label). P322 - Specific treatment (see supplemental first aid instruction on this label) P330 - Rinse mouth. P333+P313 - If skin irritation or rash occurs: Get medical advice/attention. P361+P364 - Take off immediately all contaminated clothing and wash it before reuse. P363 - Wash contaminated clothing before reuse. P370+P378 - In case of fire: Use media other than water to extinguish. P403+P233 - Store in a well-ventilated place. Keep container tightly closed. P403+P235 - Store in a well-ventilated place. Keep cool. P405 - Store locked up. P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.
-----------------------------------	---

### 2.3. Other hazards which do not result in classification

No additional information available

### 2.4. Unknown acute toxicity (GHS US)

No additional information available

# Formaldehyde 37%

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 3: Composition/Information on ingredients

#### 3.1. Substances

Not applicable

#### 3.2. Mixtures

Name	Product identifier	Conc.	GHS US classification
Water	CAS-No.: 7732-18-5	56	Not classified
formaldehyde	CAS-No.: 50-00-0	37	Flam. Gas 1, H220 Press. Gas (Liq.), H280 Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Inhalation), H331 Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1, H317 Muta. 2, H341 Carc. 1A, H350 STOT SE 3, H336
Methanol	CAS-No.: 67-56-1	7	Flam. Liq. 2, H225 Acute Tox. 4 (Oral), H302 Acute Tox. 3 (Inhalation), H331 STOT SE 1, H370

Full text of hazard classes and H-statements : see section 16

### SECTION 4: First-aid measures

#### 4.1. Description of first aid measures

First-aid measures general	: Call a physician immediately.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor/physician if you feel unwell.
First-aid measures after skin contact	: Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing. Call a physician immediately.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician immediately.
First-aid measures after ingestion	: Rinse mouth. Call a physician immediately. Do not induce vomiting.

#### 4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects	: May cause drowsiness or dizziness.
Symptoms/effects after inhalation	: Although no appropriate human or animal health effects data are known to exist, this material is expected to be an inhalation hazard.
Symptoms/effects after skin contact	: Burns. May cause an allergic skin reaction.
Symptoms/effects after eye contact	: Serious damage to eyes.
Symptoms/effects after ingestion	: Burns.

#### 4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

# Formaldehyde 37%

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 5: Fire-fighting measures

#### 5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.  
Unsuitable extinguishing media : Do not use a heavy water stream.

#### 5.2. Specific hazards arising from the chemical

Fire hazard : Flammable liquid and vapor.  
Explosion hazard : No direct explosion hazard.  
Hazardous decomposition products in case of fire : Toxic fumes may be released.

#### 5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions : Fight fire from safe distance and protected location. Do not enter fire area without proper protective equipment, including respiratory protection.  
Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

General measures : Stop leak if safe to do so. Notify authorities if product enters sewers or public waters. Absorb spillage to prevent material-damage.

##### 6.1.1. For non-emergency personnel

Protective equipment : Wear recommended personal protective equipment.  
Emergency procedures : No open flames, no sparks, and no smoking. Only qualified personnel equipped with suitable protective equipment may intervene. Do not breathe dust/fume/gas/mist/vapors/spray.

##### 6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".  
Emergency procedures : Evacuate unnecessary personnel. Stop leak if safe to do so.

#### 6.2. Environmental precautions

Avoid release to the environment. Notify authorities if product enters sewers or public waters.

#### 6.3. Methods and material for containment and cleaning up

For containment : Absorb spilled material with sand or earth. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Stop leak, if possible without risk.  
Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.  
Other information : Dispose of materials or solid residues at an authorized site.

#### 6.4. Reference to other sections

For further information refer to section 13.

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

Additional hazards when processed : Not expected to present a significant hazard under anticipated conditions of normal use.

# Formaldehyde 37%

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Precautions for safe handling	: Ensure good ventilation of the work station. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapors may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Take all necessary technical measures to avoid or minimize the release of the product on the workplace. Limit quantities of product at the minimum necessary for handling and limit the number of exposed workers. Provide local exhaust or general room ventilation. Floors, walls and other surfaces in the hazard area must be cleaned regularly. Do not breathe dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing.
Hygiene measures	: Separate working clothes from town clothes. Launder separately. Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures	: Ground/bond container and receiving equipment.
Storage conditions	: Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.
Packaging materials	: Store always product in container of same material as original container.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

Methanol (67-56-1)	
<b>USA - ACGIH - Occupational Exposure Limits</b>	
Local name	Methanol
ACGIH OEL TWA	200 ppm
ACGIH OEL STEL	250 ppm
Remark (ACGIH)	TLV® Basis: Headache; eye dam; dizziness; nausea. Notations: Skin; BEI
Regulatory reference	ACGIH 2024
<b>USA - ACGIH - Biological Exposure Indices</b>	
Local name	Methanol
BEI	15 mg/l Parameter: Methanol - Medium: urine - Sampling time: End of shift - Notations: B, Ns
Regulatory reference	ACGIH 2024
<b>USA - OSHA - Occupational Exposure Limits</b>	
Local name	Methyl alcohol
OSHA PEL TWA	260 mg/m <sup>3</sup> 200 ppm
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1

### 8.2. Appropriate engineering controls

Appropriate engineering controls	: Ensure good ventilation of the work station.
Environmental exposure controls	: Avoid release to the environment.

# Formaldehyde 37%

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 8.3. Individual protection measures/Personal protective equipment

#### Personal protective equipment:

Wear recommended personal protective equipment.

<b>Hand protection:</b>
Protective gloves
<b>Eye protection:</b>
Safety glasses
<b>Skin and body protection:</b>
Wear suitable protective clothing
<b>Respiratory protection:</b>
[In case of inadequate ventilation] wear respiratory protection.

#### Personal protective equipment symbol(s):



## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Color	: Colorless
Odor	: Irritating/pungent odour
Odor threshold	: 1 ppm
pH	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: Not applicable.
Vapor pressure	: No data available
Relative vapor density at 20°C	: No data available
Relative density	: 1.1
Density	: 1.1 g/ml
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available

<b>Methanol</b>	
Boiling point	65 °C (1013 hPa)
Flash point	10 °C (Closed cup, 1013 hPa, EU Method A.9: Flash-Point)

# Formaldehyde 37%

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Methanol	
Auto-ignition temperature	455 °C (1013 hPa, DIN 51794: Self-ignition temperature, T1)
Vapor pressure	128 hPa (20 °C)
Vapor pressure at 50°C	552 hPa

### 9.2. Other information

No additional information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Flammable liquid and vapor.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

### 10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

### 10.5. Incompatible materials

No additional information available

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity (oral) : Toxic if swallowed.  
Acute toxicity (dermal) : Toxic in contact with skin.  
Acute toxicity (inhalation) : Inhalation:dust,mist: Harmful if inhaled.

Formaldehyde 37%	
ATE US (oral)	266.03 mg/kg body weight
ATE US (dermal)	810.811 mg/kg body weight
ATE US (dust, mist)	1.136 mg/l/4h

formaldehyde (50-00-0)	
ATE US (oral)	100 mg/kg body weight
ATE US (dermal)	300 mg/kg body weight
ATE US (gases)	700 ppmV/4h
ATE US (vapors)	3 mg/l/4h
ATE US (dust, mist)	0.5 mg/l/4h

# Formaldehyde 37%

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

<b>Methanol (67-56-1)</b>	
LD50 oral rat	1187 – 2769 mg/kg body weight (BASF test, Rat, Male / female, Experimental value, 15-35 % aqueous solution, Oral, 7 day(s))
LD50 dermal rabbit	17100 mg/kg (Rabbit, Inconclusive, insufficient data, Dermal)
LC50 Inhalation - Rat	128.2 mg/l air (BASF test, 4 h, Rat, Male / female, Experimental value, Inhalation (vapours), 14 day(s))
ATE US (oral)	1187 mg/kg body weight
ATE US (dermal)	17100 mg/kg body weight
ATE US (gases)	700 ppmV/4h
ATE US (vapors)	3 mg/l/4h
ATE US (dust, mist)	0.5 mg/l/4h

Skin corrosion/irritation : Causes severe skin burns.

<b>Methanol (67-56-1)</b>	
pH	No data available in the literature

Serious eye damage/irritation : Causes serious eye damage.

<b>Methanol (67-56-1)</b>	
pH	No data available in the literature

Respiratory or skin sensitization : May cause an allergic skin reaction.

Germ cell mutagenicity : Suspected of causing genetic defects.

Carcinogenicity : May cause cancer.

<b>formaldehyde (50-00-0)</b>	
IARC group	1 - Carcinogenic to humans
National Toxicity Program (NTP) Status	Known Human Carcinogens

Reproductive toxicity : Not classified

STOT-single exposure : Causes damage to organs. May cause drowsiness or dizziness.

<b>formaldehyde (50-00-0)</b>	
STOT-single exposure	May cause drowsiness or dizziness.

<b>Methanol (67-56-1)</b>	
STOT-single exposure	Causes damage to organs.

STOT-repeated exposure : Not classified

Aspiration hazard : Not classified

Viscosity, kinematic : No data available

Symptoms/effects : May cause drowsiness or dizziness.

Symptoms/effects after inhalation : Although no appropriate human or animal health effects data are known to exist, this material is expected to be an inhalation hazard.

Symptoms/effects after skin contact : Burns. May cause an allergic skin reaction.

Symptoms/effects after eye contact : Serious damage to eyes.

Symptoms/effects after ingestion : Burns.

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - general : Before neutralisation, the product may represent a danger to aquatic organisms.



# Formaldehyde 37%

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Methanol (67-56-1)	
LC50 - Fish [1]	15400 mg/l (EPA 660/3 - 75/009, 96 h, Lepomis macrochirus, Flow-through system, Fresh water, Experimental value, Lethal)
EC50 - Crustacea [1]	18260 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 96 h, Daphnia magna, Semi-static system, Fresh water, Experimental value, Locomotor effect)
EC50 96h - Algae [1]	22000 mg/l (OECD 201: Alga, Growth Inhibition Test, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, Growth rate)
NOEC (chronic)	208 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC chronic fish	446.7 mg/l Test organisms (species): Pimephales promelas Duration: '28 d'

### 12.2. Persistence and degradability

Formaldehyde 37%	
Persistence and degradability	Not rapidly degradable
formaldehyde (50-00-0)	
Persistence and degradability	Not rapidly degradable
Methanol (67-56-1)	
Persistence and degradability	Readily biodegradable in the soil, Readily biodegradable in water.
Biochemical oxygen demand (BOD)	0.6 – 1.12 g O <sub>2</sub> /g substance
Chemical oxygen demand (COD)	1.42 g O <sub>2</sub> /g substance
ThOD	1.5 g O <sub>2</sub> /g substance
Water (7732-18-5)	
Persistence and degradability	Not rapidly degradable

### 12.3. Bioaccumulative potential

Methanol (67-56-1)	
BCF - Fish [1]	1 – 4.5 (72 h, Cyprinus carpio, Static system, Fresh water, Experimental value)
Partition coefficient n-octanol/water (Log Pow)	-0.77 (Experimental value)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).

### 12.4. Mobility in soil

Methanol (67-56-1)	
Mobility in soil	2.75 Source: HSDB
Surface tension	No data available in the literature
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	-0.89 – -0.21 (log Koc, Calculated value)
Ecology - soil	Highly mobile in soil.

### 12.5. Other adverse effects

No additional information available

# Formaldehyde 37%

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 13: Disposal considerations

#### 13.1. Disposal methods

Regional waste regulation	: Disposal must be done according to official regulations.
Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Sewage disposal recommendations	: Disposal must be done according to official regulations.
Product/Packaging disposal recommendations	: Disposal must be done according to official regulations.
Additional information	: Flammable vapors may accumulate in the container. Do not re-use empty containers.

### SECTION 14: Transport information

In accordance with DOT / TDG / IMDG / IATA

#### 14.1. UN number

DOT NA No	: UN2209
UN-No. (TDG)	: UN2209
UN-No. (IMDG)	: 2209
UN-No. (IATA)	: 2209

#### 14.2. UN proper shipping name

Proper Shipping Name (DOT)	: Formaldehyde solutions
Proper Shipping Name (TDG)	: FORMALDEHYDE SOLUTION
Proper Shipping Name (IMDG)	: FORMALDEHYDE SOLUTION
Proper Shipping Name (IATA)	: Formaldehyde solution

#### 14.3. Transport hazard class(es)

##### DOT

Transport hazard class(es) (DOT)	: 8
Hazard labels (DOT)	: 8



##### TDG

Transport hazard class(es) (TDG)	: 8
Hazard labels (TDG)	: 8



##### IMDG

Transport hazard class(es) (IMDG)	: 8
Hazard labels (IMDG)	: 8



##### IATA

Transport hazard class(es) (IATA)	: 8
Hazard labels (IATA)	: 8

# Formaldehyde 37%

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations



### 14.4. Packing group

Packing group (DOT)	: III
Packing group (TDG)	: III
Packing group (IMDG)	: III
Packing group (IATA)	: III

### 14.5. Environmental hazards

Other information : No supplementary information available.

### 14.6. Special precautions for user

#### DOT

UN-No.(DOT)	: UN2209
DOT Special Provisions (49 CFR 172.102)	: IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672). T4 - 2.65 178.274(d)(2) Normal..... 178.275(d)(3) TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = $97 / 1 + a (tr - tf)$ Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling.
DOT Packaging Exceptions (49 CFR 173.xxx)	: 154
DOT Packaging Non Bulk (49 CFR 173.xxx)	: 203
DOT Packaging Bulk (49 CFR 173.xxx)	: 241
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	: 5 L
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	: 60 L

#### TDG

UN-No. (TDG)	: UN2209
Explosive Limit and Limited Quantity Index	: 5 L
Excepted quantities (TDG)	: E1
Passenger Carrying Road Vehicle or Passenger Carrying Railway Vehicle Index	: 5 L
Emergency Response Guide (ERG) Number	: 132

#### IMDG

Limited quantities (IMDG)	: 5 L
Excepted quantities (IMDG)	: E1
Packing instructions (IMDG)	: P001, LP01
IBC packing instructions (IMDG)	: IBC03
Tank instructions (IMDG)	: T4
Tank special provisions (IMDG)	: TP1
EmS-No. (Fire)	: F-A - FIRE SCHEDULE Alfa - GENERAL FIRE SCHEDULE
EmS-No. (Spillage)	: S-B - SPILLAGE SCHEDULE Bravo - CORROSIVE SUBSTANCES
Stowage category (IMDG)	: A
Properties and observations (IMDG)	: Colourless, clear liquid, with a suffocating pungent odour. Usually stabilized with methyl alcohol. Miscible with water. Causes burns to skin, eyes and mucous membranes.

#### IATA

PCA Excepted quantities (IATA)	: E1
--------------------------------	------

# Formaldehyde 37%

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

PCA Limited quantities (IATA)	: Y841
PCA limited quantity max net quantity (IATA)	: 1L
PCA packing instructions (IATA)	: 852
PCA max net quantity (IATA)	: 5L
CAO packing instructions (IATA)	: 856
CAO max net quantity (IATA)	: 60L
Special provision (IATA)	: A803
ERG code (IATA)	: 8i

### 14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

## SECTION 15: Regulatory information

### 15.1. US Federal regulations

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.

formaldehyde ...%	CAS-No. 50-00-0	37%
Methanol	CAS-No. 67-56-1	7%

#### formaldehyde (50-00-0)

Listed on EPA Hazardous Air Pollutant (HAPS)

CERCLA RQ	100 lb
RQ (Reportable quantity, section 304 of EPA's List of Lists)	100 lb
SARA Section 302 Threshold Planning Quantity (TPQ)	500 lb

#### Methanol (67-56-1)

Listed on EPA Hazardous Air Pollutant (HAPS)

CERCLA RQ	5000 lb
-----------	---------

### 15.2. International regulations

#### CANADA

#### formaldehyde (50-00-0)

Listed on the Canadian DSL (Domestic Substances List)

#### Methanol (67-56-1)

Listed on the Canadian DSL (Domestic Substances List)

#### Water (7732-18-5)

Listed on the Canadian DSL (Domestic Substances List)

# Formaldehyde 37%

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### EU-Regulations

No additional information available


### National regulations

formaldehyde (50-00-0)
Listed on IARC (International Agency for Research on Cancer) Listed as carcinogen on NTP (National Toxicology Program) Listed on INSQ (Mexican National Inventory of Chemical Substances)

Methanol (67-56-1)
Listed on INSQ (Mexican National Inventory of Chemical Substances)

Water (7732-18-5)
Listed on INSQ (Mexican National Inventory of Chemical Substances)

### 15.3. US State regulations

 **WARNING:** This product can expose you to formaldehyde, which is known to the State of California to cause cancer, and Methanol, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

Component	State or local regulations
formaldehyde(50-00-0)	U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List
Methanol(67-56-1)	U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List

### SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Full text of H-phrases	
H220	Extremely flammable gas
H225	Highly flammable liquid and vapor
H226	Flammable liquid and vapor
H280	Contains gas under pressure; may explode if heated
H301	Toxic if swallowed
H302	Harmful if swallowed
H311	Toxic in contact with skin
H314	Causes severe skin burns and eye damage
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H331	Toxic if inhaled
H332	Harmful if inhaled
H336	May cause drowsiness or dizziness


# Formaldehyde 37%

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Full text of H-phrases	
H341	Suspected of causing genetic defects
H350	May cause cancer
H370	Causes damage to organs

- NFPA health hazard : 3 - Materials that, under emergency conditions, can cause serious or permanent injury.
- NFPA fire hazard : 2 - Materials that must be moderately heated or exposed to relatively high ambient temperatures before ignition can occur.
- NFPA reactivity : 0 - Material that in themselves are normally stable, even under fire conditions.



Safety Data Sheet (SDS), USA

The above information is believed to be correct but does not purport to be all-inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. EDM3 shall not be liable for any damage resulting from handling.