

### SECTION 1: Identification

#### 1.1. Identification

Product form : Mixture  
Product name : Isopropyl Alcohol 70%  
Product code : 400634, 400780

#### 1.2. Recommended use and restrictions on use

Use of the substance/mixture : For laboratory and manufacturing use only  
For professional use only  
Restrictions on use : Not for food, drug or household use

#### 1.3. Supplier

EDM 3, LLC  
3611 St Johns Bluff Road, Suite 1  
Jacksonville, FL 32224  
T 800-638-2625, Monday-Friday: 8:00 AM-5:00 PM

#### 1.4. Emergency telephone number

Emergency number : INFOTRAC at 1-800-535-5053 (Domestic within the USA and Canada) or 1-352-323-3500  
(International callers may call collect), 24 hours/day, 7 days/week.

### SECTION 2: Hazard(s) identification

#### 2.1. Classification of the substance or mixture


##### GHS US classification

Flammable liquids Category 2	H225	Highly flammable liquid and vapor
Serious eye damage/eye irritation Category 2	H319	Causes serious eye irritation
Specific target organ toxicity – Single exposure, Category 3, Narcosis	H336	May cause drowsiness or dizziness

Full text of H statements : see section 16

#### 2.2. GHS Label elements, including precautionary statements

##### GHS US labeling

Hazard pictograms (GHS US) : 

Signal word (GHS US) : Danger

Hazard statements (GHS US) : H225 - Highly flammable liquid and vapor  
H319 - Causes serious eye irritation  
H336 - May cause drowsiness or dizziness

Precautionary statements (GHS US) : P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P233 - Keep container tightly closed.  
P240 - Ground/Bond container and receiving equipment.  
P241 - Use explosion-proof electrical/ventilating/lighting equipment.  
P242 - Use only non-sparking tools.  
P243 - Take precautionary measures against static discharge.  
P261 - Avoid breathing dust/fume/gas/mist/vapors/spray.  
P264 - Wash hands, forearms and face thoroughly after handling.

# Isopropyl Alcohol 70%

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P271 - Use only outdoors or in a well-ventilated area.  
P280 - Wear protective gloves/protective clothing/eye protection/face protection.  
P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.  
P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing.  
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P312 - Call a poison center or doctor if you feel unwell.  
P337+P313 - If eye irritation persists: Get medical advice/attention.  
P370+P378 - In case of fire: Use media other than water to extinguish.  
P403+P233 - Store in a well-ventilated place. Keep container tightly closed.  
P403+P235 - Store in a well-ventilated place. Keep cool.  
P405 - Store locked up.  
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

### 2.3. Other hazards which do not result in classification

No additional information available

### 2.4. Unknown acute toxicity (GHS US)

No additional information available

## SECTION 3: Composition/Information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Product identifier	Conc.	GHS US classification
2-propanol	CAS-No.: 67-63-0	≥ 69.3	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336 Aquatic Chronic 4, H413
Water	CAS-No.: 7732-18-5	30	Not classified

Full text of hazard classes and H-statements : see section 16

## SECTION 4: First-aid measures

### 4.1. Description of first aid measures

First-aid measures general : Call a poison center/doctor/physician if you feel unwell.  
First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.  
First-aid measures after skin contact : Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing.  
First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.  
First-aid measures after ingestion : Call a poison center/doctor/physician if you feel unwell.

### 4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects : May cause drowsiness or dizziness.  
Symptoms/effects after inhalation : Although no appropriate human or animal health effects data are known to exist, this material is expected to be an inhalation hazard.  
Symptoms/effects after skin contact : None under normal conditions.

# Isopropyl Alcohol 70%

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Symptoms/effects after eye contact : Eye irritation.  
Symptoms/effects after ingestion : None under normal conditions.

### 4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

## SECTION 5: Fire-fighting measures

### 5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.  
Unsuitable extinguishing media : Do not use a heavy water stream.

### 5.2. Specific hazards arising from the chemical

Fire hazard : Highly flammable liquid and vapor.  
Explosion hazard : No direct explosion hazard.  
Hazardous decomposition products in case of fire : Toxic fumes may be released.

### 5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions : Fight fire from safe distance and protected location. Do not enter fire area without proper protective equipment, including respiratory protection.  
Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

General measures : Stop leak if safe to do so. Notify authorities if product enters sewers or public waters. Absorb spillage to prevent material-damage.

#### 6.1.1. For non-emergency personnel

Protective equipment : Wear recommended personal protective equipment.  
Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid breathing dust/fume/gas/mist/vapors/spray. Avoid contact with skin and eyes.

#### 6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".  
Emergency procedures : Evacuate unnecessary personnel. Stop leak if safe to do so.

### 6.2. Environmental precautions

Avoid release to the environment.

### 6.3. Methods and material for containment and cleaning up

For containment : Absorb spilled material with sand or earth. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Stop leak, if possible without risk.  
Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.  
Other information : Dispose of materials or solid residues at an authorized site.

### 6.4. Reference to other sections

For further information refer to section 13.

# Isopropyl Alcohol 70%

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

Additional hazards when processed	: Not expected to present a significant hazard under anticipated conditions of normal use.
Precautions for safe handling	: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapors may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Use only outdoors or in a well-ventilated area. Avoid breathing dust/fume/gas/mist/vapors/spray. Avoid contact with skin and eyes.
Hygiene measures	: Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

#### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures	: Ground/bond container and receiving equipment.
Storage conditions	: Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.
Packaging materials	: Store always product in container of same material as original container.

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

##### 2-propanol (67-63-0)

##### USA - ACGIH - Occupational Exposure Limits

ACGIH OEL TWA	200 ppm
ACGIH OEL STEL	400 ppm

#### 8.2. Appropriate engineering controls

Appropriate engineering controls	: Ensure good ventilation of the work station.
Environmental exposure controls	: Avoid release to the environment.

#### 8.3. Individual protection measures/Personal protective equipment

##### Personal protective equipment:

Wear recommended personal protective equipment.

##### Hand protection:

Protective gloves

##### Eye protection:

Safety glasses

##### Skin and body protection:

Wear suitable protective clothing

##### Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

# Isopropyl Alcohol 70%

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### Personal protective equipment symbol(s):



## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Color	: Colorless
Odor	: Alcohol odour
Odor threshold	: No data available
pH	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: Not applicable.
Vapor pressure	: No data available
Relative vapor density at 20°C	: No data available
Relative density	: No data available
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available

2-propanol	
Boiling point	83 °C (1013 hPa)
Flash point	12 °C (Closed cup)
Auto-ignition temperature	399 °C (T2)
Vapor pressure	44 hPa (20 °C)
Vapor pressure at 50°C	236 hPa (Antoine equation)

### 9.2. Other information

No additional information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Highly flammable liquid and vapor.

### 10.2. Chemical stability

Stable under normal conditions.

# Isopropyl Alcohol 70%

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

### 10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

### 10.5. Incompatible materials

No additional information available

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified  
Acute toxicity (dermal) : Not classified  
Acute toxicity (inhalation) : Not classified

#### 2-propanol (67-63-0)

LD50 oral rat	5840 mg/kg body weight (Equivalent or similar to OECD 401, Rat, Experimental value, Oral, 14 day(s))
LD50 dermal rabbit	16400 ml/kg (Equivalent or similar to OECD 402, 24 h, Rabbit, Experimental value, Dermal, 14 day(s))
LC50 Inhalation - Rat [ppm]	> 10000 ppm (Equivalent or similar to OECD 403, 6 h, Rat, Male / female, Experimental value, Inhalation (vapours), 14 day(s))
ATE US (oral)	5840 mg/kg body weight
ATE US (dermal)	12890400 mg/kg body weight

Skin corrosion/irritation : Not classified

#### 2-propanol (67-63-0)

pH	No data available in the literature
----	-------------------------------------

Serious eye damage/irritation : Causes serious eye irritation.

#### 2-propanol (67-63-0)

pH	No data available in the literature
----	-------------------------------------

Respiratory or skin sensitization : Not classified  
Germ cell mutagenicity : Not classified  
Carcinogenicity : Not classified

#### 2-propanol (67-63-0)

IARC group	3 - Not classifiable
------------	----------------------

Reproductive toxicity : Not classified

STOT-single exposure : May cause drowsiness or dizziness.

#### 2-propanol (67-63-0)

STOT-single exposure	May cause drowsiness or dizziness.
----------------------	------------------------------------

STOT-repeated exposure : Not classified

Aspiration hazard : Not classified

Viscosity, kinematic : No data available

# Isopropyl Alcohol 70%

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

2-propanol (67-63-0)	
Viscosity, kinematic	2.66 mm <sup>2</sup> /s (25 °C, Estimated value)
Symptoms/effects	: May cause drowsiness or dizziness.
Symptoms/effects after inhalation	: Although no appropriate human or animal health effects data are known to exist, this material is expected to be an inhalation hazard.
Symptoms/effects after skin contact	: None under normal conditions.
Symptoms/effects after eye contact	: Eye irritation.
Symptoms/effects after ingestion	: None under normal conditions.

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms or to cause long-term adverse effects in the environment.

2-propanol (67-63-0)	
LC50 - Fish [1]	9640 – 10000 mg/l (Equivalent or similar to OECD 203, 96 h, Pimephales promelas, Flow-through system, Fresh water, Experimental value, Lethal)

### 12.2. Persistence and degradability

Isopropyl Alcohol 70%	
Persistence and degradability	Not rapidly degradable
2-propanol (67-63-0)	
Persistence and degradability	Biodegradable in the soil, Biodegradable in the soil under anaerobic conditions, Readily biodegradable in water.
Biochemical oxygen demand (BOD)	1.19 g O <sub>2</sub> /g substance
Chemical oxygen demand (COD)	2.23 g O <sub>2</sub> /g substance
ThOD	2.4 g O <sub>2</sub> /g substance
Water (7732-18-5)	
Persistence and degradability	Not rapidly degradable

### 12.3. Bioaccumulative potential

2-propanol (67-63-0)	
BCF - Fish [1]	1015 (BCFBAF v3.01, Estimated value)
Partition coefficient n-octanol/water (Log Pow)	0.05 (Weight of evidence approach, 25 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

### 12.4. Mobility in soil

2-propanol (67-63-0)	
Surface tension	No data available (test not performed)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	0.185 – 0.541 (log Koc, SRC PCKOCWIN v2.0, Calculated value)
Ecology - soil	Highly mobile in soil.

# Isopropyl Alcohol 70%

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 12.5. Other adverse effects

No additional information available

## SECTION 13: Disposal considerations

### 13.1. Disposal methods

Regional waste regulation	:	Disposal must be done according to official regulations.
Waste treatment methods	:	Dispose of contents/container in accordance with licensed collector's sorting instructions.
Sewage disposal recommendations	:	Disposal must be done according to official regulations.
Product/Packaging disposal recommendations	:	Disposal must be done according to official regulations.
Additional information	:	Flammable vapors may accumulate in the container. Do not re-use empty containers.

## SECTION 14: Transport information

In accordance with DOT / TDG / IMDG / IATA

### 14.1. UN number

DOT NA No	:	UN1219
UN-No. (TDG)	:	UN1219
UN-No. (IMDG)	:	1219
UN-No. (IATA)	:	1219

### 14.2. UN proper shipping name

Proper Shipping Name (DOT)	:	Isopropyl alcohol
Proper Shipping Name (TDG)	:	ISOPROPYL ALCOHOL
Proper Shipping Name (IMDG)	:	ISOPROPANOL (ISOPROPYL ALCOHOL)
Proper Shipping Name (IATA)	:	Isopropyl alcohol

### 14.3. Transport hazard class(es)

#### DOT

Transport hazard class(es) (DOT)	:	3
Hazard labels (DOT)	:	3



#### TDG

Transport hazard class(es) (TDG)	:	3
Hazard labels (TDG)	:	3



#### IMDG

Transport hazard class(es) (IMDG)	:	3
Hazard labels (IMDG)	:	3





# Isopropyl Alcohol 70%

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### IATA

Transport hazard class(es) (IATA) : 3  
Hazard labels (IATA) : 3



### 14.4. Packing group

Packing group (DOT) : II  
Packing group (TDG) : II  
Packing group (IMDG) : II  
Packing group (IATA) : II

### 14.5. Environmental hazards

Other information : No supplementary information available.

### 14.6. Special precautions for user

#### DOT

UN-No.(DOT) : UN1219  
DOT Special Provisions (49 CFR 172.102) : IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized.  
T4 - 2.65 178.274(d)(2) Normal..... 178.275(d)(3)  
TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling =  $97 / 1 + a (tr - tf)$  Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling.  
DOT Packaging Exceptions (49 CFR 173.xxx) : 4b;150  
DOT Packaging Non Bulk (49 CFR 173.xxx) : 202  
DOT Packaging Bulk (49 CFR 173.xxx) : 242  
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : 5 L  
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 60 L  
DOT Vessel Stowage Location : B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this section is exceeded.

#### TDG

UN-No. (TDG) : UN1219  
Explosive Limit and Limited Quantity Index : 1 L  
Excepted quantities (TDG) : E2  
Passenger Carrying Road Vehicle or Passenger Carrying Railway Vehicle Index : 5 L  
Emergency Response Guide (ERG) Number : 129

#### IMDG

Limited quantities (IMDG) : 1 L  
Excepted quantities (IMDG) : E2  
Packing instructions (IMDG) : P001  
IBC packing instructions (IMDG) : IBC02  
Tank instructions (IMDG) : T4  
Tank special provisions (IMDG) : TP1  
EmS-No. (Fire) : F-E - FIRE SCHEDULE Echo - NON-WATER-REACTIVE FLAMMABLE LIQUIDS

# Isopropyl Alcohol 70%

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

EmS-No. (Spillage) : S-D - SPILLAGE SCHEDULE Delta - FLAMMABLE LIQUIDS  
Stowage category (IMDG) : B  
Flash point (IMDG) : 12°C c.c.  
Properties and observations (IMDG) : Colourless, mobile liquid. Flashpoint: 12°C c.c. Explosive limits: 2% to 12%. Miscible with water.

### IATA

PCA Excepted quantities (IATA) : E2  
PCA Limited quantities (IATA) : Y341  
PCA limited quantity max net quantity (IATA) : 1L  
PCA packing instructions (IATA) : 353  
PCA max net quantity (IATA) : 5L  
CAO packing instructions (IATA) : 364  
CAO max net quantity (IATA) : 60L  
Special provision (IATA) : A180  
ERG code (IATA) : 3L

### 14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

## SECTION 15: Regulatory information

### 15.1. US Federal regulations

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.

2-propanol	CAS-No. 67-63-0	≥ 69.3%
------------	-----------------	---------

### 15.2. International regulations

#### CANADA

##### 2-propanol (67-63-0)

Listed on the Canadian DSL (Domestic Substances List)

##### Water (7732-18-5)

Listed on the Canadian DSL (Domestic Substances List)

#### EU-Regulations

No additional information available

#### National regulations

##### 2-propanol (67-63-0)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

##### Water (7732-18-5)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

# Isopropyl Alcohol 70%

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

Component	State or local regulations
2-propanol(67-63-0)	U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List

### SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Full text of H-phrases	
H225	Highly flammable liquid and vapor
H319	Causes serious eye irritation
H336	May cause drowsiness or dizziness
H413	May cause long lasting harmful effects to aquatic life

NFPA health hazard


: 2 - Materials that, under emergency conditions, can cause temporary incapacitation or residual injury.

NFPA fire hazard

: 3 - Liquids and solids (including finely divided suspended solids) that can be ignited under almost all ambient temperature conditions.

NFPA reactivity

: 0 - Material that in themselves are normally stable, even under fire conditions.



Safety Data Sheet (SDS), USA

The above information is believed to be correct but does not purport to be all-inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. EDM3 shall not be liable for any damage resulting from handling.