

# Safety Data Sheet

Wright-Giemsa Stain Pack

Revision Date: 1/1/2020

## 1. PRODUCT AND COMPANY IDENTIFICATION

**1.1 Product identifier** Trade name: Hematology Stain Pack, Wright-Giemsa Stain  
Product code(s): 400232

**1.2 Relevant identified use** Laboratory Reagent

**1.3 Supplier** EDM 3, LLC  
3611 St Johns Bluff Road, Suite 1  
Jacksonville, FL 32224  
800-638-2625  
Monday-Friday: 8:00 -5:00 PM

**1.4 In case of a medical emergency or a spill, call:** INFOTRAC at 1-800-535-5053 (Domestic within the USA and Canada)  
or 1-352-323-3500 (International callers may call collect), 24  
hours/day, 7 days/week.

**This product is a kit which contains the following; refer to the SDS data for each of the components listed.**

**Component Name:** Wright Stain Solution  
**Component Identifier:** 400232A

**Component Name:** Buffer Solution  
**Component Identifier:** 400232B

**Component Name:** Rinse Solution  
**Component Identifier:** 400232C

## 2A. COMPONENT AND HAZARDS IDENTIFICATION

**2A.1 Component Identifier** Wright Stain Pack – Solution A  
Component Code: 400232A

**2A.2 Classification of the substance or mixture**

**Hazard statement(s):**

**Danger!**  
Highly flammable liquid and vapor.  
Toxic if swallowed or in contact with skin  
Causes skin irritation.  
Causes serious eye damage.  
Toxic if inhaled.  
Causes damage to organs.

## 2A.3 GHS Label elements, including precautionary statements



**Danger!**

### Precautionary statement(s):

**Danger!**

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Do not breathe dust/ fume/ gas/ mist/ vapors/ spray.

Wear protective gloves/ eye protection/ face protection.

If swallowed: Immediately call a poison center or doctor/ physician.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

## 2A.4 WHMIS Classification

B-2 Flammable Liquid

## 2A.5 NFPA Rating

Health hazard: 1

Fire: 3

Reactivity Hazard: 0

## 2A.6 Target Organs

Eyes, Kidney, Liver, Heart, Central nervous system, Blood, Optic nerve

## 3A. COMPOSITION/INFORMATION ON INGREDIENTS

3A.1 Components	Name	CAS number	% by weight
	Methanol	67-56-1	100
	Wright Stain	68988-92-1	<1
	Methylene Blue	7720-79-3	<1
	Eosin	17372-68-4	<1
	Inhibitor	660-68-4	Trace

## 4A. FIRST AID MEASURES

### 4A.1 General Information

<b>Eye contact:</b>	Check for and remove any contact lenses. Immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical attention immediately.
<b>Skin contact:</b>	In case of contact, flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash clothing before reuse. Clean shoes thoroughly before reuse. Get medical attention immediately.
<b>Inhalation:</b>	Move exposed person to fresh air. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. Loosen tight clothing such as a collar, tie, belt or waistband. Get medical attention immediately.
<b>Ingestion:</b>	Call medical doctor or poison control center immediately. Wash out mouth with water. Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical attention immediately.

## 5A. FIREFIGHTING MEASURES

- 5A.1 Extinguishing media:** Use dry chemical, CO<sub>2</sub>, water spray (fog) or foam. Not suitable, do not use water jet.
- 5A.2 Special hazards:** Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
- 5A.3 Hazardous Products:** Flammable liquid. In a fire or if heated, a pressure increase will occur and the container may burst with the risk of a subsequent explosion. Run-off to sewer may create fire or explosion hazard.
- 5A.4 Special protective equipment for fire-fighters:** Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.
- 5A.5 Special remarks on explosion hazards:** Vapor may cause flash fire. Vapors may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back.

## 6A. ACCIDENTAL RELEASE MEASURES

- 6A.1 Personal precautions:** No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Do not breathe vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment (see Section 8).
- 6A.2 Environmental precaution:** Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
- 6A.3 Clean up:** Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13). Use spark-proof tools and explosion-proof equipment. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see section 1 for emergency contact information and section 13 for waste disposal. Dilute with water and mop up if water-soluble or absorb with an inert dry material and place in an appropriate waste disposal container.

## 7A. HANDLING AND STORAGE

- 7A.1 Safe Handling:** Do not get in eyes, on skin or clothing. Do not breathe vapor or mist. Do not ingest. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use non-sparking tools. Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by grounding and bonding containers and equipment before transferring material. Use empty containers to retain product, residue can be hazardous. Do not reuse container.
- 7A.2 Storage:** Store in accordance with local regulations. Store in a segregated and approved area. Store in original container, protected from direct sunlight. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

## 8A. EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8A.1 Control Parameters

**Methanol:**

**Exposure limits**  
**ACGIH (United States, 1994). Absorbed through skin.**  
 TWA: 262 mg/m<sup>3</sup>  
 STEL: 328 mg/m<sup>3</sup>  
**OSHA (United States, 1989). Absorbed through skin.**  
 TWA: 260 mg/m<sup>3</sup>  
 STEL: 325 mg/m<sup>3</sup>  
**ACGIH TLV (United States, 1/2008). Absorbed through skin.**  
 TWA: 200 ppm 8 hour(s).  
 TWA: 262 mg/m<sup>3</sup> 8 hour(s).  
 STEL: 250 ppm 15 minute(s).  
 STEL: 328 mg/m<sup>3</sup> 15 minute(s).  
**OSHA PEL 1989 (United States, 3/1989). Absorbed through skin.**  
 TWA: 200 ppm 8 hour(s).  
 TWA: 260 mg/m<sup>3</sup> 8 hour(s).  
 STEL: 250 ppm 15 minute(s).  
 STEL: 325 mg/m<sup>3</sup> 15 minute(s).  
**NIOSH REL (United States, 6/2008). Absorbed through skin.**  
 TWA: 200 ppm 10 hour(s).  
 TWA: 260 mg/m<sup>3</sup> 10 hour(s).  
 STEL: 250 ppm 15 minute(s).  
 STEL: 325 mg/m<sup>3</sup> 15 minute(s).  
**OSHA PEL (United States, 11/2006).**  
 TWA: 200 ppm 8 hour(s).  
 TWA: 260 mg/m<sup>3</sup> 8 hour(s).

**8A.2 Engineering measures:** Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

**8A.3 Hygiene measures:** Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

**8A.4 Personal protection**

**Respiratory:** Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

**Hands:** Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Recommended: neoprene

**Eyes:** Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists or dusts. Recommended: splash goggles

**Skin:** Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Recommended: lab coat

**8A.5 Environmental exposure controls:** Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

## 9A. PHYSICAL AND CHEMICAL PROPERTIES

### 9A.1 Information on basic physical and chemical properties

<b>Physical state:</b>	Liquid.	<b>Color:</b>	Dark blue
<b>Flash Point:</b>	Open Cup: 15.85C (60.5F)	<b>Auto-ignition temperature:</b>	464C (867.2F)
<b>Flammable limits:</b>	Lower: 6%, Upper: 36.5%	<b>Odor:</b>	Characteristic, alcohol-like.
<b>Molecular Weight:</b>	32.05 g/mole	<b>Molecular formula:</b>	C-H4-O
<b>pH:</b>	Not available.	<b>Boiling/condensation point:</b>	64.5C (148.1F)
<b>Melting/freezing point:</b>	-97.8C (-144F)	<b>Relative density:</b>	0.792

<b>Vapor pressure:</b>	12.9 IPa (97 mm Hg)	<b>Vapor density:</b>	1.11 [Air=1]
<b>Volatility:</b>	100% (v/v)	<b>Odor threshold:</b>	100ppm
<b>Evaporation rate:</b>	2.1 (butyl acetate=1)	<b>VOC:</b>	100 % (w/w)
<b>Solubility:</b>	Not available	<b>Decomposition temperature:</b>	Not Available

## 10A. STABILITY AND REACTIVITY

- 10A.1 Chemical stability:** The product is stable.
- 10A.2 Possibility of hazardous reactions:** Under normal conditions of storage and use, hazardous reactions will not occur.
- 10A.3 Hazardous polymerization:** Under normal conditions of storage and use, hazardous polymerization will not occur.
- 10A.4 Conditions to avoid:** Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition
- 10A.5 Materials to avoid:** Highly reactive or incompatible with the following materials: oxidizing materials. Reactive or incompatible with the following materials: metals and acids.
- 10A.6 Hazardous decomposition products:** Under normal conditions of storage and use, hazardous decomposition products should not occur
- 10A.7 Conditions of reactivity:** Highly flammable in the presence of the following materials or conditions: open flames, sparks and static discharge, heat, shocks and mechanical impacts and oxidizing materials. Highly explosive in the presence of the following materials or conditions: open flames, sparks and static discharge, heat, shocks and mechanical impacts and oxidizing materials. Vapor may cause flash fire. Vapors may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back.

## 11A. TOXICOLOGICAL INFORMATION

### 11A.1 Information on toxicological effects Acute Toxicity

<b>Oral LD50:</b>	no data available
<b>Inhalation LC50:</b>	no data available
<b>Dermal LD50:</b>	no data available
<b>Other information on acute toxicity:</b>	no data available
<b>Skin corrosion/irritation:</b>	no data available
<b>Serious eye damage/eye irritation:</b>	no data available
<b>Respiratory or skin sensitization:</b>	no data available
<b>Germ cell mutagenicity:</b>	no data available
<b>Specific target organ toxicity, single exposure (Globally Harmonized System):</b>	no data available
<b>Specific target organ toxicity, repeated exposure (Globally Harmonized System):</b>	no data available
<b>Aspiration hazard:</b>	no data available

### 11A.2 Potential Health Effects

- Inhalation:** Toxic if inhaled. Causes respiratory tract irritation.
- Ingestion:** Toxic if swallowed.
- Skin:** Toxic if absorbed through skin. Causes skin irritation.
- Eyes:** Causes eye irritation.

### 11A.2 Signs and Symptoms of Exposure

Warning: Contains methanol. May be fatal or cause blindness if swallowed. Cannot be made nonpoisonous. Effects due to ingestion may include: Gastrointestinal disturbance, Headache, Nausea, Vomiting, Dizziness, Weakness, Confusion, Drowsiness, Unconsciousness, To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

## 12A. ECOLOGICAL INFORMATION

### 12A.1 Ecotoxicity Data (United States) Methanol

Species	Period	Result
Daphia Magna (EC50)	48 hour/hours	>10000 mg/l
Oncorhynchus myKiss (EC50)	48 hour/hours	13200 mg/l
Lepomis Macrochirus (EC50)	48 hour/hours	16000 mg/l
Daphia Magna (LC50)	96 hour/hours	>100 mg/l
Pimephales Promelas (LC 50)	96 hour/hours	>100 mg/l
<i>Lepomis Macrochirus (LC50)</i>	<i>96 hour/hours</i>	<i>15400 mg/l</i>

#### 12A.2 Environmental Precautions:

No known significant effects or critical hazardous. The products of degradation are less toxic than the product itself.

### 13A. DISPOSAL CONSIDERATIONS

**13A.1 Methods:** The information presented only applies to the material as supplied. The identification based on characteristic(s) or listing may not apply if the material has been used or otherwise contaminated. It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste identification and disposal methods in compliance with applicable regulations. Disposal should be in accordance with applicable regional, national, local laws and regulations.

### 14A. TRANSPORT INFORMATION

#### Land Transport DOT (US)

UN No. UN1230  
 Proper Shipping Name Methanol Solution  
 Hazard Class 3  
 Packing Group II

#### TDG

UN No. UN1230  
 Proper Shipping Name Methanol Solution  
 Hazard Class 3  
 Subsidiary Hazard Class 6.1  
 Packing Group II

#### IATA

UN No. UN1230  
 Proper Shipping Name Methanol Solution  
 Hazard Class 3  
 Subsidiary Hazard Class 6.1  
 Packing Group II

#### IMDG/IMP

UN No. UN1230  
 Proper Shipping Name Methanol Solution  
 Hazard Class 3  
 Subsidiary Hazard Class 6.1  
 Packing Group II

### 15A. REGULATORY INFORMATION

#### United States

**HCS Classification:** Flammable liquid, Highly toxic material, Irritating material, Target organ effects

#### U.S. Federal regulations:

**TSCA 8(a) IUR:** Partial exemption  
**United States inventory (TSCA 8b):**

Listed on inventory.

**SARA 302/304/311/312 extremely hazardous substances:** No products were found.

**SARA 302/304 emergency planning and notification:** No products were found.

**SARA 302/304/311/312 hazardous chemicals:** Methanol

**SARA 311/312 MSDS distribution - chemical inventory - hazard identification:**

Methanol: Fire hazard, Immediate (acute) health hazard, Delayed (chronic) health hazard

Clean Water Act (CWA) 307: No products were found.

Clean Water Act (CWA) 311: No products were found.

**Clean Air Act (CAA) 112 accidental release prevention:** No products were found.

Clean Air Act (CAA) 112 regulated flammable substances: No products were found.  
Clean Air Act (CAA) 112 regulated toxic substances: No products were found.

**DEA List I & II Chemicals  
(Precursor Chemicals):**

Not listed

**SARA 313**

**Form R - Reporting**

**Requirements:**

**Supplier notification:**

**Product name**

**CAS number**

**Concentration**

Methanol

64-17-5

99 - 100

Methanol

64-17-5

99 - 100

SARA 313 notifications must not be detached from the MSDS and any copying and redistribution of the MSDS shall include copying and redistribution of the notice attached to copies of the MSDS subsequently redistributed.

**RTK:** Methanol CAS 64-56-1

Connecticut, Massachusetts, New Jersey, Pennsylvania, Rhode Island

**PROP 65 California:** Methanol

**WHMIS (Canada):**

Class B-2: Flammable Liquid  
Class D-1A: Material causing immediate and serious toxic effects (Very toxic).

**Canadian lists:**

Class D-2B: Material causing other toxic effects (Toxic).  
**CEPA Toxic substances:** None of the components are listed.  
**Canadian ARET:** None of the components are listed.  
**Canadian NPRI:** None of the components are listed.  
**Alberta Designated Substances:** None of the components are listed.  
**Ontario Designated Substances:** None of the components are listed.  
**Quebec Designated Substances:** None of the components are listed.

**CEPA DSL / CEPA NDSL:**

**CERCLA:**

All components are listed or exempted.  
Methyl Alcohol: RQ 5000 lb


*This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.*

**International regulations**

**International lists:**

**Australia inventory (AICS):** All components are listed or exempted.  
**China inventory (IECSC):** All components are listed or exempted.  
**Japan inventory:** Not determined.  
**Korea inventory:** Not determined.  
**New Zealand Inventory of Chemicals (NZIoC):** All components are listed or exempted.  
**Philippines inventory (PICCS):** All components are listed or exempted.

**16A. OTHER INFORMATION**



**National Fire Protection Association (U.S.A.)**

**Disclaimer**

The above information is believed to be correct but does not purport to be all-inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. EDM3 shall not be liable for any damage resulting from handling.

## 2B. COMPONENT AND HAZARDS IDENTIFICATION

**2B.1 Component Identifier** Wright Giemsa Stain Pack – Solution B  
Component Code: 400232B

### 2B.2 Classification of the substance or mixture

**Hazard statement:** Does not contain dangerous substances according to the Global Harmonized System (GHS).

### 2B.3 GHS Label elements, including precautionary statements

**No label elements (pictorials) required**

#### Precautionary statement(s):

Inhalation: May be harmful if inhaled. May cause respiratory tract irritation.  
Skin: Wear protective gloves/ eye protection/ face protection.  
Ingestion: May be harmful if swallowed. Call a doctor/ physician.  
If in eyes: May cause irritation. Rinse cautiously with water for several minutes.

### 2B.4 WHMIS Classification

Not classified.

### 2B.5 NFPA Rating

Health hazard: 0  
Fire: 0  
Reactivity Hazard: 0

### 2B.6 Target Organs

Eyes, Kidney, Liver, Heart, Central nervous system, Blood, Optic nerve

## 3B. COMPOSITION/INFORMATION ON INGREDIENTS

3B.1 Components	Name	CAS number	% by weight
	Water	7732-18-5	>99
	Sodium Phosphate, Dibasic	7558-79-4	<1
	Potassium Phosphate, Mono	7778-77-0	<1
	Methyl Paraben	99-76-3	<1

## 4B. FIRST AID MEASURES

### 4B.1 General Information

**Eye contact:** Check for and remove any contact lenses. Immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical attention immediately.

**Skin contact:** In case of contact, flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash clothing before reuse. Clean shoes thoroughly before reuse. Get medical attention immediately.

**Inhalation:** Move exposed person to fresh air. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. Loosen tight clothing such as a collar, tie, belt or waistband. Get medical attention immediately.

**Ingestion:** Call medical doctor or poison control center immediately. Wash out mouth with water. Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical attention immediately.



## 5B. FIREFIGHTING MEASURES

**5B.1 Firefighting measures:** Follow guidance described in 5A.

## 6B. ACCIDENTAL RELEASE MEASURES

**6B.1 Personal precautions:** No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Do not breathe vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment (see Section 8).

**6B.2 Environmental precaution:** Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

**6B.3 Clean up:** Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see section 1 for emergency contact information and section 13 for waste disposal. Dilute with water and mop up if water-soluble or absorb with an inert dry material and place in an appropriate waste disposal container.

## 7B. HANDLING AND STORAGE

**7B.1 Safe Handling:** Do not get in eyes, on skin or clothing. Do not breathe vapor or mist. Do not ingest. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Use empty containers to retain product, residue can be hazardous. Do not reuse container.

**7B.2 Storage:** Store in accordance with local regulations. Store in a segregated and approved area. Store in original container, protected from direct sunlight. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

## 8B. EXPOSURE CONTROLS/PERSONAL PROTECTION

**8B.2 Engineering measures:** Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits.

**8B.3 Hygiene measures:** Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

### 8B.4 Personal protection

**Respiratory:** Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

**Hands:** Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Recommended: neoprene

**Eyes:** Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists or dusts. Recommended: splash goggles

**Skin:** Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Recommended: lab coat

**8B.5 Environmental exposure controls:** Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

## 9B. PHYSICAL AND CHEMICAL PROPERTIES

### 9B.1 Information on basic physical and chemical properties

<b>Physical state:</b>	Liquid.	<b>Color:</b>	Colorless
<b>Odor:</b>	Odorless	<b>pH:</b>	6.7
<b>Boiling/condensation point:</b>	100C (212F)	<b>Melting/freezing point:</b>	Not available
<b>Relative density:</b>	1	<b>Vapor pressure:</b>	Not available
<b>Vapor density:</b>	Not available	<b>Odor threshold:</b>	Not available
<b>Evaporation rate:</b>	0.36 (water)	<b>VOC:</b>	0%
<b>Solubility:</b>	Soluble in water		

## 10B. STABILITY AND REACTIVITY

**10B.1 Chemical stability:** The product is stable.

**10B.2 Possibility of hazardous reactions:** Under normal conditions of storage and use, hazardous reactions will not occur.

**10B.3 Hazardous polymerization:** Under normal conditions of storage and use, hazardous polymerization will not occur.

**10b.4 Conditions to avoid:** No specific data.

**10B.5 Hazardous decomposition products:** Under normal conditions of storage and use, hazardous decomposition products should not occur

## 11B. TOXICOLOGICAL INFORMATION

<b>Carcinogenicity:</b>	No known significant effects or critical hazards.
<b>Mutagenicity:</b>	No known significant effects or critical hazards.
<b>Teratogenicity:</b>	No known significant effects or critical hazards.

## 12B. ECOLOGICAL INFORMATION

**12B.1 Environmental Precautions:** No known significant effects or critical hazardous. The products of degradation are less toxic than the product itself.

## 13B. DISPOSAL CONSIDERATIONS

**13B.1 Methods:** The information presented only applies to the material as supplied. The identification based on characteristic(s) or listing may not apply if the material has been used or otherwise contaminated. It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste identification and disposal methods in compliance with applicable regulations. Disposal should be in accordance with applicable regional, national, local laws and regulations.

## 14B. TRANSPORT INFORMATION

Not regulated.

## 15B. REGULATORY INFORMATION

## United States

**HCS Classification:** Not regulated

**U.S. Federal regulations:** **TSCA 8(a) IUR:** Not determined  
**United States inventory (TSCA 8b):**  
All components are listed or exempted.  
All components of this product are listed on or compliant with the TSCA inventory.  
**SARA 302/304/311/312 extremely hazardous substances:** No products were found.  
**SARA 302/304 emergency planning and notification:** No products were found.  
**SARA 302/304/311/312 hazardous chemicals:** No products were found.  
**SARA 311/312 MSDS distribution - chemical inventory - hazard identification:**  
No products were found.  
Clean Water Act (CWA) 307: No products were found.  
Clean Water Act (CWA) 311: Sodium Phosphate, Dibasic  
**Clean Air Act (CAA) 112 accidental release prevention:** No products were found.  
Clean Air Act (CAA) 112 regulated flammable substances: No products were found.  
Clean Air Act (CAA) 112 regulated toxic substances: No products were found.

## DEA List I & II Chemicals (Precursor Chemicals):

Not listed

**RTK:** Not Listed

Connecticut, Massachusetts, New Jersey, NY, Pennsylvania, Rhode Island

## WHMIS (Canada):

**Not controlled**

## Canadian lists:

**CEPA Toxic substances:** None of the components are listed.  
**Canadian ARET:** None of the components are listed.  
**Canadian NPRI:** None of the components are listed.  
**Alberta Designated Substances:** None of the components are listed.  
**Ontario Designated Substances:** None of the components are listed.  
**Quebec Designated Substances:** None of the components are listed.

## CEPA DSL / CEPA NDSL:

All components are listed or exempted.

*This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.*

## International regulations

### International lists:

**Australia inventory (AICS):** All components are listed or exempted.  
**China inventory (IECSC):** All components are listed or exempted.  
**Japan inventory:** Not determined.  
**Korea inventory:** Not determined.  
**New Zealand Inventory of Chemicals (NZIoC):** All components are listed or exempted.  
**Philippines inventory (PICCS):** All components are listed or exempted.

## 16B. OTHER INFORMATION



### Disclaimer

The above information is believed to be correct but does not purport to be all-inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. EDM3 shall not be liable for any damage resulting from handling.

## 2C. COMPONENT AND HAZARDS IDENTIFICATION

### 2C.1 Component Identifier

Wright Giemsa Stain Pack – Solution C  
Component Code: 400232C

### 2C.2 Classification of the substance or mixture

#### Hazard statement(s):

**Danger!**

Highly flammable liquid and vapor.  
Toxic if swallowed or in contact with skin  
Causes skin irritation.  
Causes serious eye damage.  
Toxic if inhaled.  
Causes damage to organs.

### 2C.3 GHS Label elements, including precautionary statements



**Danger!**

#### Precautionary statement(s):

**Danger!**

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.  
Do not breathe dust/ fume/ gas/ mist/ vapors/ spray.  
Wear protective gloves/ eye protection/ face protection.  
If swallowed: Immediately call a poison center or doctor/ physician.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

## 2C.4 WHMIS Classification

B-2 Flammable Liquid

## 2C.5 NFPA Rating

Health hazard: 1

Fire: 3

Reactivity Hazard: 0

## 2C.6 Target Organs

Eyes, Kidney, Liver, Heart, Central nervous system, Blood, Optic nerve

## 3C. COMPOSITION/INFORMATION ON INGREDIENTS

3C.1 Components	Name	CAS number		% by weight
	Methanol	67-56-1	~10	
	Water	7732-18-5		~90
	Sodium Phosphate, Dibasic	7558-79-4		<1
	Potassium Phosphate, Mono	7778-77-0		<1
	Inhibitor	26628-22-8		Trace

## 4C. FIRST AID MEASURES

### 4C.1 General Information

<b>Eye contact:</b>	Check for and remove any contact lenses. Immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical attention immediately.
<b>Skin contact:</b>	In case of contact, flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash clothing before reuse. Clean shoes thoroughly before reuse. Get medical attention immediately.
<b>Inhalation:</b>	Move exposed person to fresh air. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. Loosen tight clothing such as a collar, tie, belt or waistband. Get medical attention immediately.
<b>Ingestion:</b>	Call medical doctor or poison control center immediately. Wash out mouth with water. Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical attention immediately.

## 5C. FIREFIGHTING MEASURES

**5C.1 Extinguishing media:** Use dry chemical, CO<sub>2</sub>, water spray (fog) or foam. Not suitable, do not use water jet.

**5C.2 Special hazards:** Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

**5C.3 Hazardous Products:** Flammable liquid. In a fire or if heated, a pressure increase will occur and the container may burst with the risk of a subsequent explosion. Run-off to sewer may create fire or explosion hazard.

**5C.4 Special protective equipment for fire-fighters:** Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

**5C.5 Special remarks on explosion hazards:** Vapor may cause flash fire. Vapors may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back.

## 6C. ACCIDENTAL RELEASE MEASURES

- 6C.1 Personal precautions:** No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Do not breathe vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment (see Section 8).
- 6C.2 Environmental precaution:** Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
- 6C.3 Clean up:** Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13). Use spark-proof tools and explosion-proof equipment. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see section 1 for emergency contact information and section 13 for waste disposal. Dilute with water and mop up if water-soluble or absorb with an inert dry material and place in an appropriate waste disposal container.

## 7C. HANDLING AND STORAGE

- 7C.1 Safe Handling:** Do not get in eyes, on skin or clothing. Do not breathe vapor or mist. Do not ingest. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use non-sparking tools. Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by grounding and bonding containers and equipment before transferring material. Use empty containers to retain product, residue can be hazardous. Do not reuse container.
- 7C.2 Storage:** Store in accordance with local regulations. Store in a segregated and approved area. Store in original container, protected from direct sunlight. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

## 8C. EXPOSURE CONTROLS/PERSONAL PROTECTION

**Methanol:**

**Exposure limits**

**ACGIH (United States, 1994). Absorbed through skin.**  
TWA: 262 mg/m<sup>3</sup>  
STEL: 328 mg/m<sup>3</sup>

**OSHA (United States, 1989). Absorbed through skin.**  
TWA: 260 mg/m<sup>3</sup>  
STEL: 325 mg/m<sup>3</sup>

**ACGIH TLV (United States, 1/2008). Absorbed through skin.**  
TWA: 200 ppm 8 hour(s).  
TWA: 262 mg/m<sup>3</sup> 8 hour(s).  
STEL: 250 ppm 15 minute(s).  
STEL: 328 mg/m<sup>3</sup> 15 minute(s).

**OSHA PEL 1989 (United States, 3/1989). Absorbed through skin.**  
TWA: 200 ppm 8 hour(s).  
TWA: 260 mg/m<sup>3</sup> 8 hour(s).  
STEL: 250 ppm 15 minute(s).  
STEL: 325 mg/m<sup>3</sup> 15 minute(s).

**NIOSH REL (United States, 6/2008). Absorbed through skin.**  
TWA: 200 ppm 10 hour(s).  
TWA: 260 mg/m<sup>3</sup> 10 hour(s).  
STEL: 250 ppm 15 minute(s).  
STEL: 325 mg/m<sup>3</sup> 15 minute(s).

**OSHA PEL (United States, 11/2006).**

TWA: 200 ppm 8 hour(s).

TWA: 260 mg/m<sup>3</sup> 8 hour(s).

**8C.2 Engineering measures:** Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

**8C.3 Hygiene measures:** Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

**8C.4 Personal protection**

**Respiratory:** Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

**Hands:** Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Recommended: neoprene

**Eyes:** Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists or dusts. Recommended: splash goggles

**Skin:** Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Recommended: lab coat

**8C.5 Environmental exposure controls:** Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

**9C. PHYSICAL AND CHEMICAL PROPERTIES****9C.1 Information on basic physical and chemical properties**

<b>Physical state:</b>	Liquid.	<b>Color:</b>	Colorless
<b>Flash Point:</b>	Open Cup: 15.85C (60.5F)	<b>Auto-ignition temperature:</b>	644C (867.2F)
<b>Flammable limits:</b>	Lower: 6%, Upper: 36.5%	<b>Odor:</b>	Characteristic, alcohol-like.
<b>Molecular Weight:</b>	32.05 g/mole	<b>Molecular formula:</b>	C-H4-O
<b>pH:</b>	6.5	<b>Boiling/condensation point:</b>	64.5C (148.1F)
<b>Melting/freezing point:</b>	-97.8C (-144F)	<b>Relative density:</b>	0.792
<b>Vapor pressure:</b>	12.9 IPa (97 mm Hg)	<b>Vapor density:</b>	1.11 [Air=1]
<b>Volatility:</b>	10% (v/v)	<b>Odor threshold:</b>	100ppm
<b>Evaporation rate:</b>	2.1 (butyl acetate=1)	<b>VOC:</b>	10% (w/w)
<b>Solubility:</b>	Not available	<b>Decomposition temperature:</b>	Not Available

**10C. STABILITY AND REACTIVITY**

**10C.1 Chemical stability:** The product is stable.

**10C.2 Possibility of hazardous reactions:** Under normal conditions of storage and use, hazardous reactions will not occur.

**10C.3 Hazardous polymerization:** Under normal conditions of storage and use, hazardous polymerization will not occur.

**10C.4 Conditions to avoid:** Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition

**10C.5 Materials to avoid:** Highly reactive or incompatible with the following materials: oxidizing materials. Reactive or incompatible with the following materials: metals and acids.

### 10C.6 Hazardous decomposition

**products:** Under normal conditions of storage and use, hazardous decomposition products should not occur

**10C.7 Conditions of reactivity:** Highly flammable in the presence of the following materials or conditions: open flames, sparks and static discharge, heat, shocks and mechanical impacts and oxidizing materials. Highly explosive in the presence of the following materials or conditions: open flames, sparks and static discharge, heat, shocks and mechanical impacts and oxidizing materials. Vapor may cause flash fire. Vapors may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back.

## 11C. TOXICOLOGICAL INFORMATION

### 11C.1 Information on toxicological effects

#### Acute Toxicity

<b>Oral LD50:</b>	no data available
<b>Inhalation LC50:</b>	no data available
<b>Dermal LD50:</b>	no data available
<b>Other information on acute toxicity:</b>	no data available
<b>Skin corrosion/irritation:</b>	no data available
<b>Serious eye damage/eye irritation:</b>	no data available
<b>Respiratory or skin sensitization:</b>	no data available
<b>Germ cell mutagenicity:</b>	no data available
<b>Specific target organ toxicity, single exposure (Globally Harmonized System):</b>	no data available
<b>Specific target organ toxicity, repeated exposure (Globally Harmonized System):</b>	no data available
<b>Aspiration hazard:</b>	no data available

### 11C.2 Potential Health Effects

**Inhalation:** Toxic if inhaled. Causes respiratory tract irritation.

**Ingestion:** Toxic if swallowed.

**Skin:** Toxic if absorbed through skin. Causes skin irritation.

**Eyes:** Causes eye irritation.

### 11C.2 Signs and Symptoms of Exposure

Warning: Contains methanol. May be fatal or cause blindness if swallowed. Cannot be made nonpoisonous. Effects due to ingestion may include: Gastrointestinal disturbance, Headache, Nausea, Vomiting, Dizziness, Weakness, Confusion, Drowsiness, Unconsciousness, To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

## 12C. ECOLOGICAL INFORMATION

### 12C.1 Ecotoxicity Data (United States) Methanol

<u>Species</u>	<u>Period</u>	<u>Result</u>
Daphia Magna (EC50)	48 hour/hours	>10000 mg/l
Oncorhynchus myKiss (EC50)	48 hour/hours	13200 mg/l
Lepomis Macrochirus (EC50)	48 hour/hours	16000 mg/l
Daphia Magna (LC50)	96 hour/hours	>100 mg/l
Pimephales Promelas (LC 50)	96 hour/hours	>100 mg/l
<i>Lepomis Macrochirus (LC50)</i>	<i>96 hour/hours</i>	<i>15400 mg/l</i>

### 12C.2 Environmental Precautions:

No known significant effects or critical hazardous. The products of degradation are less toxic than the product itself.

## 13C. DISPOSAL CONSIDERATIONS

**13C.1 Methods:** The information presented only applies to the material as supplied. The identification based on characteristic(s) or listing may not apply if the material has been used or otherwise contaminated. It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste identification and disposal methods in compliance with applicable regulations. Disposal should be in accordance with applicable regional, national, local laws and regulations.

## 14C. TRANSPORT INFORMATION



## Land Transport DOT (US)

**UN No.** UN1230  
**Proper Shipping Name** Methanol Solution  
**Hazard Class** 3  
**Packing Group** II

## TDG

**UN No.** UN1230  
**Proper Shipping Name** Methanol Solution  
**Hazard Class** 3  
**Subsidiary Hazard Class 6.1**  
**Packing Group** II

## IATA

**UN No.** UN1230  
**Proper Shipping Name** Methanol Solution  
**Hazard Class** 3  
**Subsidiary Hazard Class 6.1**  
**Packing Group** II

## IMDG/IMP

**UN No.** UN1230  
**Proper Shipping Name** Methanol Solution  
**Hazard Class** 3  
**Subsidiary Hazard Class 6.1**  
**Packing Group** II

## 15C. REGULATORY INFORMATION

### United States

**HCS Classification:** Flammable liquid, Highly toxic material, Irritating material, Target organ effects

**U.S. Federal regulations:**

**TSCA 8(a) IUR:** Partial exemption  
**United States inventory (TSCA 8b):**  
Listed on inventory.

**SARA 302/304/311/312 extremely hazardous substances:** No products were found.

**SARA 302/304 emergency planning and notification:** No products were found.

**SARA 302/304/311/312 hazardous chemicals:** Methanol

**SARA 311/312 MSDS distribution - chemical inventory - hazard identification:**

Methanol: Fire hazard, Immediate (acute) health hazard, Delayed (chronic) health hazard

Clean Water Act (CWA) 307: No products were found.

Clean Water Act (CWA) 311: No products were found.

**Clean Air Act (CAA) 112 accidental release prevention:** No products were found.

Clean Air Act (CAA) 112 regulated flammable substances: No products were found.

Clean Air Act (CAA) 112 regulated toxic substances: No products were found.

**DEA List I & II Chemicals  
(Precursor Chemicals):**

Not listed

### SARA 313

	Product name	CAS number	Concentration
<b>Form R - Reporting Requirements:</b>	Methanol	67-56-1	~10%
<b>Supplier notification:</b>	Methanol	67-56-1	~10%

SARA 313 notifications must not be detached from the MSDS and any copying and redistribution of the MSDS shall include copying and redistribution of the notice attached to copies of the MSDS subsequently redistributed.

**RTK:** Methanol CAS 67-56-1

Connecticut, Massachusetts, New Jersey, NY, Pennsylvania, Rhode Island

### WHMIS (Canada):

Class B-2: Flammable Liquid  
Class D-1A: Material causing immediate and serious toxic effects (Very toxic).

### Canadian lists:

Class D-2B: Material causing other toxic effects (Toxic).  
**CEPA Toxic substances:** None of the components are listed.  
**Canadian ARET:** None of the components are listed.

**Canadian NPRI:** None of the components are listed  
**Alberta Designated Substances:** None of the components are listed.  
**Ontario Designated Substances:** None of the components are listed.  
**Quebec Designated Substances:** None of the components are listed.

**CEPA DSL / CEPA NDSL:**  
**CERCLA:**

All components are listed or exempted.  
Methyl Alcohol: RQ 5000 lb

*This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.*

**International regulations**  
**International lists:**

**Australia inventory (AICS):** All components are listed or exempted.  
**China inventory (IECSC):** All components are listed or exempted.  
**Japan inventory:** Not determined.  
**Korea inventory:** Not determined.  
**New Zealand Inventory of Chemicals (NZIoC):** All components are listed or exempted.  
**Philippines inventory (PICCS):** All components are listed or exempted.

## 16C. OTHER INFORMATION



**National Fire Protection Association (U.S.A.)**

### **Disclaimer**

The above information is believed to be correct but does not purport to be all-inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. EDM3 shall not be liable for any damage resulting from handling.